

# egOS

Version:  
1.9.0

Date:  
08.12.2025



# Contents

<b>1</b>	<b>Introduction</b>	<b>2</b>
<b>2</b>	<b>Getting Started</b>	<b>3</b>
2.1	Connecting to the device	3
<b>3</b>	<b>Security Considerations</b>	<b>6</b>
3.1	Exposed Interfaces and Services	6
3.2	Device Security Features	6
3.3	Security Recommendations	7
3.4	Vulnerability Handling	7
3.5	Secure Dipsosal	8
<b>4</b>	<b>Configuration Management</b>	<b>9</b>
4.1	Command line interface	9
4.2	Presets	10
4.3	Confirmation of connectivity	10
4.4	Exporting and importing configuration	11
<b>5</b>	<b>CLI Commands</b>	<b>12</b>
5.1	Network management	12
5.2	Device	32
5.3	Firewall	60
5.4	Container management	89
5.5	Docker configuration	90
5.6	OVPN	98
5.7	Azure modules access to a device's local storage	101
5.8	Link module storage to device storage	102
5.9	iotedge command	104
<b>6</b>	<b>Web Interface</b>	<b>108</b>
6.1	EdgeGateway WebUI Documentation	108
6.2	Central Device Management via SMART EMS	113
<b>7</b>	<b>OS Updates</b>	<b>114</b>
7.1	'device swupdate' Command	114
7.2	Update Page in WebUI	114
7.3	SMART EMS	114
<b>8</b>	<b>Factory Reset</b>	<b>115</b>
8.1	Via CLI	115
8.2	Via Power button	115
<b>9</b>	<b>OSS Clearings</b>	<b>116</b>

# 1 Introduction

Welotec egOS is our Linux-based operating system for Edge Gateway Series Products. During the design phase, we focused in particular on scalable edge applications and maximum IT security. We guarantee the constant reliability and security of our system through regular updates and upgrades. It is optimised for cloud connectivity and container deployment. As an open platform, our egOS is designed for your customised solutions and enables software-driven innovation.

This manual provides information on how to configure Welotec Edge Gateways running egOS. Please visit our [documentation homepage](#) for hardware manuals for specific devices.

## 2 Getting Started

Please read the Chapter “Security Considerations” carefully before first use!


### 2.1 Connecting to the device

#### 2.1.1 Power supply

Please check the hardware manual for your Edge Gateway model for power supply. Different hardware versions may use different voltages, connectors or pinouts. Connector for one hardware model, even if physically matching connector from other hardware model may be incompatible!

#### 2.1.2 Access via ethernet using SSH


- Connect your computer to the Edge Gateway’s LAN1 port using an ethernet cable
- In factory default settings the Edge Gateway’s LAN1 is set to 192.168.2.1/24
- Configure your computer’s LAN port with an IP-configuration from 192.168.2.0/24 network (for example 192.168.2.2/24)
- Establish a connection using a terminal program (e.g. PuTTY) to 192.168.2.1 with port 22(SSH) Login with user-name “admin” and password “123456”
- Change password according to prompts



For security reasons it is crucial to perform first SSH connection using either direct cable connection between your computer and EG, or within secure network in which it impossible for the attacker to perform man in the middle attack. During first connection EG will advertise to SSH client (e.g. PuTTY) its public key. Users shall ensure that during any future connections exactly the same key is being shown to their SSH client, otherwise it is possible there is man in the middle attack in progress.

### 2.1.3 Access via COM-port using serial CLI

- In factory default settings the CLI is accessible via COM1 on the EdgeGateway
- Connect your computer's COM port to EdgeGateway's COM1 using a RS232 null modem cable
- Establish a connection using a terminal program (e.g. PuTTY) with your local COM-port and baud rate of 115200
- Login with username "admin" and password "123456"
- Change password according to prompts



# 3 Security Considerations

This section provides detailed security recommendations to help you configure your Welotec IIoT Edge Gateway for optimal security in your IIoT deployment.

## 3.1 Exposed Interfaces and Services

In factory default the following interfaces and services are exposed and accessible:

Interface	Services Listening	Factory Default Setting	Comment
LAN1	SSH-Server	Static IP address: 192.168.2.1/24	This is the only interface with preconfigured static IP address.
LAN2 ... n	SSH-Server, DHCP-client	DHCP client ready to obtain IP configuration	This is the only interface that uses DHCP out-of-the-box.
Local Console	CLI	CLI	With attached keyboard and display
COM1	CLI	CLI redirected to COM port	/

Then LAN interface can be configured individually to a static IP-configuration or to obtain IP configuration from a DHCP server. Access Local Console as well as Console Redirect to COM-ports can be deactivated in configuration.

## 3.2 Device Security Features

### 3.2.1 Secure Boot and Encrypted Storage

Edge Gateways provide Secure Boot and the system and user data storage is fully encrypted with help of the TPM of the device. Boot partition is plain text and all of the boot data is secured against tampering with strong cryptographic signatures. Check the release notes about models and versions supporting this feature.

### 3.2.2 Firewall

The firewall of the device allows to limit the communication of the device to the necessary minimum for your use case. Please refer to Firewall Section for further details.

### 3.2.3 Security updates and patch management

Welotec is providing updates for the egOS regularly. Please refer to OS Updates Section for futher details.

## 3.3 Security Recommendations

### 3.3.1 Passwords

Strong passwords are the first line of defense against unauthorized access. You can disable Password based access to the device and only use SSH-host key authentication. If you want to use password based access it is recommended to:

- Change the factory default password on first login
- Use passwords with a minimum length of 12 characters or more
- Use a combination of uppercase and lowercase letters, numbers, and special characters (e.g., !@#\$%^&\*)
- Do not use easily guessable patterns, such as sequences (e.g., “123456”, “abcdef”), repeated characters (e.g., “aaaaaa”), or dictionary words

### 3.3.2 Network Segmentation

Network segmentation is a critical security practice that involves dividing a network into smaller, isolated subnets or zones. This approach limits the impact of a security breach by preventing an attacker from moving laterally through the network and accessing critical systems. In an IIoT environment, this is crucial for protecting sensitive industrial control systems (ICS) and other operational technology (OT) assets. Use the Welotec IIoT Edge Gateway's networking capabilities to create separate network segments. Methods for implementing segmentation:

- VLANs (Virtual LANs): Create VLANs to segment network traffic at Layer 2. This allows you to isolate devices on the same physical network.
- Subnets: Use IP subnets to divide the network at Layer 3. This provides logical separation and allows for different routing and firewall policies.
- Firewall Rules: Configure the gateway's firewall to control traffic flow between different segments. Implement strict rules to allow only necessary communication and block all other traffic.
- Routing: Use static routes or dynamic routing protocols to control how traffic is routed between segments. Ensure that routing is configured to enforce security policies.

### 3.3.3 Secure remote access

Welotec is providing a software solution to enable Secure Remote Access: VPN Security Suite Please visit our home-page for further information.

### 3.3.4 Physical security of the device

- Place the device in a locked cabinet or implement other physical security measures to avoid manipulation of the device
- Limit the access to the device by disabling local login using the device 'set\_local\_console'-command

## 3.4 Vulnerability Handling

Welotec has implemented a Coordinated Vulnerability Disclosure Policy - please visit the following site for further details: <https://welotec.com/pages/coordinated-vulnerability-disclosure-policy>

## 3.5 Secure Diposal

To securely dispose the device please reset it to factory defaults using the options provided here: Factory reset. This will delete all configuration, containers and user data on the device.

# 4 Configuration Management

The Edge Gateway provides the following options for device configuration:

- A Command Line Interface (CLI) including exporting and importing of full device configuration JSON
- Web Interface (disabled in factory default settings) for configuring device connectivity and supporting import of a full device configuration JSON
- Central device management solution SMART EMS - please visit [our homepage](#) for further information.

## 4.1 Command line interface

Following general commands are available:

```
device          generic configuration (not put into any of the specific commands or affecting multiple of the specific domains at the same time)
docker         container management
docker-config   global docker configuration related actions (like exporting config of all containers in EG)
nm             network management in general
fw             firewall configuration
ovpn           vpn tunnels management
```

Each of the commands has multiple subcommands and parameters described in this document.

### 4.1.1 Runtime help

Each command provides -h option which can be used at both: command level and subcommand level for quick refresh of what commands do and what parameters they take. Note that CLI command descriptions in this document are based mostly on runtime help system (so whenever you execute a CLI command with option -help the output will be identical to part of this document).

### 4.1.2 Autocompletion

For ease of working with parameters commands support bash autocompletion. To trigger autocompletion in bash use 'Tab' key. Note that bash autocompletion sometimes falls back to the file names even if file name is not really expected by the command syntax.

### 4.1.3 Argument globbing

Because of daemon based approach in some cases it is not trivial to provide autocompletion of dynamically changable values (like names of firewall rules), but globbing may be often used instead — when documentation of command says that globbing is allowed, patterns may be used instead of exact values. An asterisk (\*) matches any string (including no characters at all), a question mark (?) matches any single character. Note that this is identical with shell globbing and shell may match a file name if a pattern is used. To prevent it, whole argument needs to be quoted or just special characters need to be prepended with backslash (\).

Compare below sequence of commands:

```

admin@eg ~> ls
admin@eg ~> fw preset list di*      # no files matching so di* is forwarded to daemon
{
  "saved": [
    "disabled"
  ],
  "being_edited": []
}
admin@eg ~> touch di.txt
admin@eg ~> fw preset list di*      # di* matches di.txt so daemon sees di.txt
{
  "saved": [],
  "being_edited": []
}
admin@eg ~> fw preset list 'di*'  # prevent file matching manually, daemon sees di*
{
  "saved": [
    "disabled"
  ],
  "being_edited": []
}
admin@eg ~>

```

## 4.2 Presets

Some of the commands deal with complicated sets of rules which work as intended only if they properly cooperate — good example of such area are firewall rules. Composing working firewall step by step, each applied immediately can easily lead to erratic and invalid behaviour of firewall. Additionally, potentially more than one person can have access rights allowing for management of EG and there needs to be a way to prevent one of them doing changes incompatible with other person's changes accidentally. For such areas preset system is provided, where each preset is independent working config, but only one of the presets can be applied to the whole device at the same time. Moreover, preset can be modified only when marked as being edited, which prevents accidental applying of non-finished preset.

### 4.2.1 Editing presets

- Subcommands “preset\_edit” and “preset\_create” leave preset in state of being edited
- Only preset being edited can be modified
- There are some factory prepared presets which cannot be put into edition state
- If there is more than one preset being edited at the same time then modification commands need to be given additional optional argument with name of preset intended for modification (usually ‘-n’).

## 4.3 Confirmation of connectivity

EG is intended to be managed remotely, but some of the configuration commands can easily break connectivity to the device. Such commands after being applied require additional verification if the person who executed them still can access the device. For CLI this verification is done by displaying message — if connectivity is not lost, user will see it and will be able to respond. If there is no confirmation, changes will be rolled back. Unfortunately, in some cases rollback may not be ideal — there are multiple subsystems, so user is encouraged to always verify that configuration is as expected after such automatic rollback.

## 4.4 Exporting and importing configuration

The whole device configuration (or specific parts) can be exported to a JSON-File.

This file can be imported into other devices or deployed via SMART EMS — see get\_config and set\_config subcommands of various commands.

# 5 CLI Commands

## 5.1 Network management

This command allows to configure and check network related settings except firewall and ovpn.

This command has following subcommands:

show	show network configuration
status	show current network status
cellular_turn_on	turn on cellular modem
cellular_turn_off	turn off cellular modem
cellular_configure	add configuration on the device <b>for</b> cellular modem
wifi	manage wifi1 interface
static_ip	<b>set</b> static ip <b>for</b> network interface
dhcp	<b>set</b> dhcp on network interface
ignore_default_route	enable/disable deaftult route <b>from</b> DHCP
set_config	<b>set</b> network configuration <b>from</b> a json file
cellular_checklist	Run checks to fix cellular configuration
get_config	save network configuration <b>in</b> ./network_config.json
static_routing	Configure static routing
promiscous_mode	enable/disable promiscous mode on a given interface
dns	Manipulate EG system DNS settings.
ids	enable/disable IDS on a given interface
dhcp-server	Enable, disable <b>and</b> configure DHCP server.

Examples:

To configure cellular1 interface

```
nm cellular_configure 1 --apn internet --pin 1234
```

To turn on ceullar1

```
nm cellular_turn_on 1
```

To turn off ceullar1

```
nm cellular_turn_off 1
```

Other examples:

```
nm static_ip --name lan1 --ip 10.0.0.2 --gateway 10.0.0.1 --subnet 24 --dns 9.8.8.8
nm static_ip --name lan1 --ip 10.0.0.2 --gateway 10.0.0.1 --subnet 24 --dns 1.1.1.1,2.2.2.2
nm static_ip --name lan1 --ip 10.0.0.2 --subnet 24
nm dhcp --name lan1
```

## 5.1.1 show

Print network related configurable values of EG to console. In case of configuration which may result in dynamically changing values it also shows them at the moment when command is executed. Commands `show`, `get_config` and `status` are related to checking network configuration. The difference is on their focus. `show` focuses on showing currently configured values to human. `get_config` focuses on whole configuration backup. `status` focuses on current actual values used by system and includes also things that are not configurable (like loopback interface).

Synopsis:

```
nm show [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

Examples:

the only way to call this command

```
nm show
```

## 5.1.2 status

Same as executing classic Linux commands ‘ifconfig’ and ‘route’. Commands `show`, `get_config` and `status` are related to checking network configuration. The difference is on their focus. `show` focuses on showing currently configured values to human. `get_config` focuses on whole configuration backup. `status` focuses on current actual values used by system and includes also things that are not configurable (like loopback interface).

Synopsis:

```
nm status [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

## 5.1.3 cellular\_turn\_on

Enable connection on mobile network interface. This connection should be configured before turning on with help of `cellular_configure` command.

Synopsis:

```
nm cellular_turn_on [-h] interface
```

Detailed description of positional arguments:

```
interface  Cellular interface number
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

Examples:

to enable cellular1 interface

```
nm cellular_turn_on 1
```

to enable cellular2 interface

```
nm cellular_turn_on 2
```

## 5.1.4 cellular\_turn\_off

Disconnect mobile network interface (connected because of earlier `cellular_turn_on` command). Any active network connections going through this interface will be dropped.

Synopsis:

```
nm cellular_turn_off [-h] interface
```

Detailed description of positional arguments:

interface	Cellular interface name
-----------	-------------------------

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
------------	--

Examples:

to disable cellular1 interface

nm cellular_turn_off 1
------------------------

to disable cellular2 interface

nm cellular_turn_off 2
------------------------

## 5.1.5 cellular\_configure

Configures cellular connection parameters. Any previous configuration, will be removed, hence all of the parameters with non-default values should be provided each time this command is executed (otherwise default values will replace previously configured non-default ones). After configuration is done it can be checked with `show`, or exported with `get_config`.

Synopsis:

```
nm cellular_configure [-h] -a APN [-p PIN] [-A ACCESS_NUMBER] [-u USER]
                      [-P PASSWORD]
                      interface
```

Detailed description of positional arguments:

interface	Cellular interface number (starting <b>from</b> 1)
-----------	--

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
-a APN, --apn APN	APN name
-p PIN, --pin PIN	SIM card PIN, <b>if not</b> given means no PIN <b>is</b> configured on SIM card. PIN can only contains digits. To remove the PIN <b>from</b> the configuration, omit the " <b>--pin</b> " argument.

(continues on next page)

(continued from previous page)

```

-A ACCESS_NUMBER, --access_number ACCESS_NUMBER
  phone number of APN, if not given defults to *99***1#
-u USER, --user USER user name for APN (if not given empty user name will
  be used)
-P PASSWORD, --password PASSWORD
  password for APN (if not given empty password will be
  used)

```

Examples:

configure basic authentication using APN named ‘internet’ without PIN nor user/password authentication for cellular1 interface.

```
nm cellular_configure 1 --apn internet
```

configure authentication based on username ‘USER’ and password ‘PASSWORD’ with apn named ‘welo.vzwent’ but without PIN for SIM card for cellular2 interface

```
nm cellular_configure 2 --user USER --password PASSWORD --apn welo.vzwent
```

## 5.1.6 wifi

Manages wifi1 interface. Currently supported implementation is WiFi-Client role, which allows user to configure new connection, enable or disable it and scan for available networks.

This command has following subcommands:

```
client allows to use wifi1 interface in client role
```

Detailed description of named arguments:

```
-h, --help show this help message and exit
```

Examples:

configure and connect connection profile with AP based on ssid ‘SSID’, key ‘KEY’ with authentication ‘wpa3-sae’ for wifi1 interface

```
nm wifi client config --ssid SSID --key KEY --authentication wpa3-sae
```

enable and connect connection profile on wifi1 interface

```
nm wifi client enable
```

disable and disconnect connection profile on wifi1 interface

```
nm wifi client disable
```

scan for available wifi networks

```
nm wifi client scan
```

## client

This command has following subcommands:

scan	scan <b>for</b> available access points
enable	enable <b>and</b> connect configured profile
disable	disable <b>and</b> disconnect configured profile
config	add <b>and</b> activate a new connection profile using the given details

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
------------	--

scan

Synopsis:

```
nm wifi client scan [-h] [--rescan {auto,yes,no}]
```

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
--rescan {auto,yes,no}	used to either force <b>or</b> disable the scan regardless of how fresh the access point <b>list is</b>

enable

Synopsis:

```
nm wifi client enable [-h]
```

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
------------	--

disable

Synopsis:

```
nm wifi client disable [-h]
```

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
------------	--

config

Synopsis:

```
nm wifi client config [-h] -s SSID -k KEY -a
                      {wpa-psk,wpa2-psk,wpa3-sae}
                      [-e {auto,ccmp,tkip} [{auto,ccmp,tkip} ...]]
```

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
-s SSID, --ssid SSID	ssid to connect to
-k KEY, --key KEY	wpaX-key <b>for</b> the connection
-a {wpa-psk,wpa2-psk,wpa3-sae}, --authentication {wpa-psk,wpa2-psk,wpa3-sae}	authentication method WPA-PSK / WPA2-PSK / WPA3-SAE
-e {auto,ccmp,tkip} [{auto,ccmp,tkip} ...], --encryption {auto,ccmp,tkip} [{auto,ccmp,tkip} ...]	encryption Mode CCMP <b>and/or</b> TKIP <b>for</b> WPA / WPA2

## 5.1.7 static\_ip

Allows to configure static IP addresses on given network interface. Replaces any previous configuration of interface (for example to remove gateway execute this command with same –ip parameter as currently set, but without –gateway parameter)

Synopsis:

```
nm static_ip [-h] --name {} --ip IP [--mtu MTU] [--gateway GATEWAY]
              --subnet SUBNET [--dns DNS]
```

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
--name {}	network interface name
--ip IP	ip address
--mtu MTU	MTU
--gateway GATEWAY	gateway ( <b>if not</b> given, gateway will be <b>set</b> to null)
--subnet SUBNET	subnet mask (number of bits, so use 24 instead of 255.255.255.0)
--dns DNS	DNS to be used when interface <b>is</b> up ( <b>if not</b> given, DNS will <b>not</b> be associated <b>with</b> this interface being up <b>and</b> <b>set</b> to null). You can also add multiple DNS servers at once (comma separated).

Examples:

configure static ip 10.0.0.1/8 on lan1 without gateway!

```
nm static_ip --name lan1 --ip 10.0.0.1 --subnet 8
```

configure static ip 192.168.1.2/24 with gateway 192.168.1.1

```
nm static_ip --name lan2 --ip 192.168.1.2 --gateway 192.168.1.1
```

## 5.1.8 dhcp

Causes given network interface to use DHCP for obtaining network configuration. Any static configuration will be forgotten. First DHCP request will be sent immediately. Command will wait up to 8 seconds for connection to be up. No error reporting is performed — always verify connection status if you want to be sure DHCP worked as expected (e.g. by executing `nm {SHOW}`)

Synopsis:

```
nm dhcp [-h] --name {}
```

Detailed description of named arguments:

<code>-h, --help</code>	show this help message <b>and</b> exit
<code>--name {}</code>	device name

Examples:

use DHCP for lan2

```
nm dhcp --name lan2
```

## 5.1.9 ignore\_default\_route

Allows to ignore default route provided by DHCP (this may be required in case another default route is preferred).

Synopsis:

```
nm ignore_default_route [-h] -n NAME -i IGNORE
```

Detailed description of named arguments:

<code>-h, --help</code>	show this help message <b>and</b> exit
<code>-n NAME, --name NAME</code>	device name
<code>-i IGNORE, --ignore IGNORE</code>	Yes to ignore route <b>from</b> DHCP

Examples:

default route provided by DHCP on lan2 will be ignored

```
nm ignore_default_route --name lan2 -i yes
```

default route provided by DHCP on lan1 will be added to routing table

```
nm ignore_default_route -n lan1 --ignore no
```

## 5.1.10 set\_config

Replaces whole network configuration of EG with the one provided by json file. The file could have been generated on same or another device.

Synopsis:

```
nm set_config [-h] --filename FILENAME [--unconditionally]
```

Detailed description of named arguments:

```

-h, --help      show this help message and exit
--filename FILENAME json filename
--unconditionally Prevent connectivity checking after executing this
                     command (without this option user may be asked to
                     confirm that after command execution he has not lost
                     connection to the device, without such confirmation
                     command would be rolled back.)

```

Examples:

restore configuration from file 'network\_config.json'

```
nm set_config --filename network_config.json
```

Example config file:

```
{
  "network": {
    "cellular1": {
      "access_number": "*99***1#",
      "apn": "",
      "password": "",
      "pin": "",
      "state": "off",
      "username": ""
    },
    "lan2": {
      "dhcp": true,
      "ignore_default_route": false
    },
    "lan1": {
      "dhcp": false,
      "ip": [
        "192.168.2.1"
      ],
      "subnet": [
        "24"
      ],
      "gateway": null,
      "dns": null
    }
  },
  "static_routing": {
    "enabled": false,
    "selected": "disabled",
    "saved": {
      "disabled": {}
    },
    "edited": {}
  }
}
```

## 5.1.11 cellular\_checklist

Gather cellular state information

Synopsis:

```
nm cellular_checklist [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

## 5.1.12 get\_config

Stores whole network related config for e.g. backup purposes into file ./network\_config.json. Commands `show`, `get_config` and `status` are related to checking network configuration. The difference is on their focus. `show` focuses on showing currently configured values to human. `get_config` focuses on whole configuration backup. `status` focuses on current actual values used by system and includes also things that are not configurable (like loopback interface).

Synopsis:

```
nm get_config [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

Examples:

the only way to call this command

```
nm get_config
```

## 5.1.13 static\_routing

Manages static routing rules, both global and interface specific. Because routing rules can become quite complicated and to allow quick changes of configuration routing rules are stored in presets.

This command has following subcommands:

<code>print</code>	print contents of preset being edited (whole or just a part)
<code>add</code>	add new routing rule to edited preset
<code>remove</code>	remove rule from global or interface config in edited preset
<code>order</code>	Change order of two elements
<code>enable</code>	Enable routing rules in selected preset
<code>disable</code>	Disable routing rules added by selected preset
<code>preset_create</code>	create new preset in being_edited state
<code>preset_delete</code>	delete preset currently being_edited
<code>preset_edit</code>	mark saved preset as being_edited (allows to change its contents, but prevents selecting it as current one)
<code>preset_save</code>	mark preset being_edited as saved
<code>preset_select</code>	select saved preset for use
<code>preset_list</code>	list existing presets (both saved and being_edited)
<code>preset_print</code>	print contents of preset(s) (whole or just a part)

Detailed description of named arguments:

```
-h, --help           show this help message and exit
```

Examples:

enables static routing rules stored in currently selected preset

```
nm static_routing enable
```

add route to 192.168.0.0/24 via lan1 device

```
nm static_routing add -n 192.168.0.0 -s 24 -d lan1
```

change order of rules for lan1 device in edited preset

```
nm static_routing order -i 1 -I 2 -c lan1
```

remove rule from lan1 device in edited preset

```
nm static_routing remove -i 1 -c lan1
```

## print

Similar to preset\_print but intended to print only single currently edited preset. If there is only one preset being edited name of the preset can be skipped. If there is more than one preset being edited, name of the preset must be given and it shall match only one of them. -part argument allows to limit output, e.g. in case of huge preset.

Synopsis:

```
nm static_routing print [-h] [-n NAME] [-p PART]
```

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
-n NAME, --name NAME	Name of the preset being edited which will be affected. Shell glob patterns may be used but shall match exactly one preset. If skipped this param defaults to '*' <b>and</b> because normally only one preset is being edited, so this argument is usually skipped.
-p PART, --part PART	Part (at least container of rules) of preset which shall be printed. Whole preset will printed <b>if not</b> given.

Examples:

print contents of the one and only currently being edited preset

```
nm static_routing print
```

## add

Synopsis:

```
nm static_routing add [-h] [-m METRIC] -a NETWORK_ADDRESS -s SUBNET
                      [-v VIA] [-d DEV]
                      [-t {nat,local,unicast,broadcast,multicast,blackhole,unreachable,
              ↵throw,prohibit}]
                      [-b BIND] [-S {link,host,global}] [-n NAME] [-E]
```

Detailed description of named arguments:

```

-h, --help           show this help message and exit
-m METRIC, --metric METRIC
                  Metric of route, defaults to 100
-a NETWORK_ADDRESS, --network_address NETWORK_ADDRESS
                  Destination network address, eg. 192.168.0.1
-s SUBNET, --subnet SUBNET
                  Destination network subnet, eg. 24
-v VIA, --via VIA
                  Gateway address. Routing means that (almost)
                  unmodified IP packet is sent over selected physical
                  link within physical packet addressed to gateway ---
                  therefore gateway must be directly reachable using
                  physical (e.g. MAC for Ethernet) address on given
                  interface --- this is by default ensured by kernel by
                  refusing to add route if gateway address is not in
                  subnet configured on given interface. Note that if the
                  gateway address is same as one of configured ip
                  addresses of EG own interfaces the --bind option will
                  be implied for this rule)
-d DEV, --dev DEV
                  Device name (note that if this option is given --bind
                  is implied too), devices available in system {'eth0',
                  'lo'}
-t {nat,local,unicast,broadcast,multicast,blackhole,unreachable,throw,prohibit}, --type {nat,
local,unicast,broadcast,multicast,blackhole,unreachable,throw,prohibit}
                  Type of route, defaults to 'unicast'
-b BIND, --bind BIND
                  Bind route to specific interface. If rule is bound to
                  a specific interface system will automatically add or
                  remove this rule depending on the interface status.
                  Note that even if this option is not given manually it
                  may be implied based on --dev or --via options. Rules
                  not bound to specific interfaces are global and will
                  be applied only on EG startup or full reload of all
                  static routes.
-S {link,host,global}, --scope {link,host,global}
                  Select rule scope
-n NAME, --name NAME
                  Name of the preset being_edited which will be
                  affected. Shell glob patterns may be used but shall
                  match exactly one preset. If skipped this param
                  defaults to '*' and because normally only one preset
                  is being edited, so this argument is usually skipped.
-E, --make_edited
                  Mark saved preset as being edited one before
                  performing other actions, giving this option is the
                  same as if separate command `preset_edit` was executed
                  by the user just before this command --- it may fail
                  if preset is already being edited, or if another user
                  tried to make preset edited at the same time

```

## remove

Synopsis:

```
nm static_routing remove [-h] -c CONFIG -i ID [-n NAME] [-E]
```

Detailed description of named arguments:

```

-h, --help           show this help message and exit
-c CONFIG, --config CONFIG
                  Name of config to be affected in currently edited
                  preset eg `lan1`, `lan2`. Configs are visible after
                  executing preset_print within edited preset.

```

(continues on next page)

(continued from previous page)

<b>-i ID, --id ID</b> <b>-n NAME, --name NAME</b> <b>-E, --make_edited</b>	ID of route to be deleted in currently edited preset Name of the preset being_edited which will be affected. Shell glob patterns may be used but shall match exactly one preset. If skipped this param defaults to '*' and because normally only one preset is being edited, so this argument is usually skipped. Mark saved preset as being edited one before performing other actions, giving this option is the same as if separate command `preset_edit` was executed by the user just before this command --- it may fail if preset is already being edited, or if another user tried to make preset edited at the same time
--	---

## order

Synopsis:

```
nm static_routing order [-h] -c CONFIG -i ID -I ID [-n NAME] [-E]
```

Detailed description of named arguments:

<b>-h, --help</b> <b>-c CONFIG, --config CONFIG</b> <b>-i ID, --id ID</b> <b>-I ID, --ID ID</b> <b>-n NAME, --name NAME</b> <b>-E, --make_edited</b>	show this help message and exit Name of config to be affected in currently edited preset eg `lan1`, `lan2`. Configs are visible after executing preset_print within edited preset. ID of first rule ID of second rule Name of the preset being_edited which will be affected. Shell glob patterns may be used but shall match exactly one preset. If skipped this param defaults to '*' and because normally only one preset is being edited, so this argument is usually skipped. Mark saved preset as being edited one before performing other actions, giving this option is the same as if separate command `preset_edit` was executed by the user just before this command --- it may fail if preset is already being edited, or if another user tried to make preset edited at the same time
---	---

## enable

Synopsis:

```
nm static_routing enable [-h]
```

Detailed description of named arguments:

<b>-h, --help</b>	show this help message and exit
-------------------	---------------------------------

## disable

Synopsis:

```
nm static_routing disable [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

## preset\_create

This command creates a new preset in being\_edited state. If --source option is given the new one will be a copy of the pointed source preset. This is atomic operation – even if more than one actor can access EG at the same time they will receive error if they try to perform conflicting atomic actions. Atomic operations are: preset selection, creating new preset, saving or making preset edited, reading all presets for backup or restoring all presets from backup.

Synopsis:

```
nm static_routing preset_create [-h] [-s SOURCE] name
```

Detailed description of positional arguments:

name	Name of the preset to create. No patterns allowed.
------	--

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
-s SOURCE, --source SOURCE	Name of preset which shall be source of data <b>for</b> preset being_edited. Shell glob patterns may be used, but exactly one name must match pattern.

Examples:

create a new preset named better\_foo as a copy of good\_old\_foo

```
nm static_routing preset_create better_foo --source good_old_foo
```

## preset\_delete

This command removes existing preset. Before removal preset must be in being\_edited state (see option --make\_edited). Removed preset cannot be restored – use backup instead.

Synopsis:

```
nm static_routing preset_delete [-h] [-E] [name]
```

Detailed description of positional arguments:

name	Name of the preset being_edited which will be affected. Shell glob patterns may be used but shall match exactly one preset. If skipped this param defaults to '*' <b>and</b> because normally only one preset <b>is</b> being edited, so this argument <b>is</b> usually skipped.
------	---

Detailed description of named arguments:

```

-h, --help      show this help message and exit
-E, --make_edited  Mark saved preset as being edited one before performing
                   other actions, giving this option is the same as if
                   separate command `preset_edit` was executed by the user
                   just before this command --- it may fail if preset is
                   already being edited, or if another user tried to make
                   preset edited at the same time
  
```

Examples:

first make preset good\_old\_foo editable (this step may fail, which will prevent removal), then remove it

```
nm static_routing preset_delete good_old_foo --make_edited
```

remove better\_foo - this will fail if it is not being\_edited

```
nm static_routing preset_delete better_foo
```

remove preset which name ends with foo - this will fail if there is no such preset being edited already

```
nm static_routing preset_delete '*foo'
```

## preset\_edit

This command can be applied on saved preset to make it editable. Editable presets cannot be accidentally selected, and saved presets cannot be accidentally edited or removed. Because of this allowing to edit selected preset makes no sense — the whole idea is to prevent potentially incomplete preset from being selected. To modify selected preset you need to make a copy of it (see command `preset_create -s`), then make changes, then save and select the copy. This is atomic operation – even if more than one actor can access EG at the same time they will receive error if they try to perform conflicting atomic actions. Atomic operations are: preset selection, creating new preset, saving or making preset edited, reading all presets for backup or restoring all presets from backup. Note that after starting the edition of the preset following editions are not atomic and if more than one actor performs them at the same time result might be unexpected — it is user responsibility to ensure that second actor will not start modifying preset already in being\_edited state before first actor finished his editions!

Synopsis:

```
nm static_routing preset_edit [-h] [name]
```

Detailed description of positional arguments:

name	Name of saved preset. Shell glob patterns may be used but pattern must match exactly one preset name. If omitted defaults to '*'.
------	---

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

Examples:

make preset good\_old\_foo editable

```
nm static_routing preset_edit good_old_foo
```

## preset\_save

This command can be applied on being\_edited preset to make it saved. Optionally a new name can be given to the preset during this operation. Editable presets cannot be accidentally selected, and saved presets cannot be accidentally edited or removed. This is atomic operation – even if more than one actor can access EG at the same time they will receive error if they try to perform conflicting atomic actions. Atomic operations are: preset selection, creating new preset, saving or making preset edited, reading all presets for backup or restoring all presets from backup.

Synopsis:

```
nm static_routing preset_save [-h] [-d DESTINATION] [name]
```

Detailed description of positional arguments:

name	Name of the preset being_edited which will be affected. Shell glob patterns may be used but shall <b>match</b> exactly one preset. If skipped this param defaults to '*' <b>and</b> because normally only one preset <b>is</b> being edited, so this argument <b>is</b> usually skipped.
------	--

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
-d DESTINATION, --destination DESTINATION	Optional name under which currently being_edited preset shall be saved, <b>if not</b> given current name of preset being_edited will be used

Examples:

assuming only one preset is being edited currently save it under name new\_name

```
nm static_routing preset_save -d new_name
```

save preset which name starts with my\_ (there must be exactly one such preset in being edited state, but there may be other being edited presets whose names start differently)

```
nm static_routing preset_save 'my_*'
```

save the only being edited preset

```
nm static_routing preset_save
```

## preset\_select

This command can be applied on saved preset to apply its contents as current configuration of EG. Any previously selected preset will cease to be selected anymore. This operation may require confirmation by the user after it is applied to prevent accidental loss of communication between user and EG. If such confirmation is not received it will be rolled back. If such confirmation is required, then operation starts at the moment of execution and ends at the moment it is rolled back or committed. Selected preset cannot be made editable. This is atomic operation – even if more than one actor can access EG at the same time they will receive error if they try to perform conflicting atomic actions. Atomic operations are: preset selection, creating new preset, saving or making preset edited, reading all presets for backup or restoring all presets from backup.

Synopsis:

```
nm static_routing preset_select [-h] [--unconditionally] [name]
```

Detailed description of positional arguments:

name	Optional shell glob pattern to limit names of presets to print (defaults to '*')
------	---

Detailed description of named arguments:

-h, --help	show this help message and exit
--unconditionally	Prevent connectivity checking after executing this command (without this option user may be asked to confirm that after command execution he has not lost connection to the device, without such confirmation command would be rolled back.)

Examples:

select and apply configuration in preset location2\_config

```
nm static_routing preset_select location2_config
```

## preset\_list

Lists existing presets (optionally limiting the result to presets matching glob pattern. Useful before executing commands to which concrete name is needed, or to check if preset is saved or being edited.

Synopsis:

```
nm static_routing preset_list [-h] [name]
```

Detailed description of positional arguments:

name	Optional shell glob pattern to limit names returned (defaults to '*')
------	---

Detailed description of named arguments:

-h, --help	show this help message and exit
------------	---------------------------------

Examples:

list all presets

```
nm static_routing preset_list
```

list presets which names start with an 'a' and end with an 'x'

```
nm static_routing preset_list 'a*x'
```

## preset\_print

Prints contents of preset(s). For presets with multipart structure, if only one part is interesting output may be limited by giving the -part argument.

Synopsis:

```
nm static_routing preset_print [-h] [-p PART] [name]
```

Detailed description of positional arguments:

name	Optional shell glob pattern to limit names of presets to print (defaults to '*')
------	--

Detailed description of named arguments:

<code>-h, --help</code>	show this help message <b>and</b> exit
<code>-p PART, --part PART</code>	Part (at least container of rules) of preset which shall be printed. Whole preset will printed <b>if not</b> given.

Examples:

print contents of part foo/bar/baz in all presets

```
nm static_routing preset_print --part foo/bar/baz
```

print contents of whole foobar preset

```
nm static_routing preset_print foobar
```

## 5.1.14 promiscous\_mode

Synopsis:

```
nm promiscous_mode [-h] interface {on,off}
```

Detailed description of positional arguments:

<code>interface</code>	name of the interface
<code>{on,off}</code>	turn on/off promiscous mode on selected interface

Detailed description of named arguments:

<code>-h, --help</code>	show this help message <b>and</b> exit
-------------------------	--

Examples:

turn on promiscous mode on lan1

```
nm promiscous_mode lan1 on
```

turn off promiscous mode on lan2

```
nm promiscous_mode lan2 off
```

## 5.1.15 dns

Add and remove DNS servers to the network configuration which will be used with priority. DNS entries set in resolved.conf override those from DHCP or manual. Ensures consistent, central DNS configuration for all interfaces.

This command has following subcommands:

<code>add</code>	Add a DNS Server.
<code>delete</code>	Remove the specified DNS Server.
<code>show</code>	Show the currently configured DNS Servers.
<code>override-nic-config</code>	Enable <b>or</b> disable system DNS stub listener.

Detailed description of named arguments:

<code>-h, --help</code>	show this help message <b>and</b> exit
-------------------------	--

## add

Synopsis:

```
nm dns add [-h] ip_address
```

Detailed description of positional arguments:

```
ip_address IP Address of DNS Server.
```

Detailed description of named arguments:

```
-h, --help show this help message and exit
```

## delete

Synopsis:

```
nm dns delete [-h] ip_address
```

Detailed description of positional arguments:

```
ip_address IP Address of DNS Server.
```

Detailed description of named arguments:

```
-h, --help show this help message and exit
```

## show

Synopsis:

```
nm dns show [-h]
```

Detailed description of named arguments:

```
-h, --help show this help message and exit
```

## override-nic-config

Synopsis:

```
nm dns override-nic-config [-h] {enable,disable}
```

Detailed description of positional arguments:

```
{enable,disable}
```

Detailed description of named arguments:

```
-h, --help show this help message and exit
```

## 5.1.16 ids

Synopsis:

```
nm ids [-h] interface {enable,disable}
```

Detailed description of positional arguments:

interface	name of the interface
{enable,disable}	turn on/off IDS on selected interface

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
------------	--

Examples:

turn on IDS on lan1

```
nm ids lan1 enable
```

turn off IDS on lan2

```
nm ids lan2 disable
```

## 5.1.17 dhcp-server

This command has following subcommands:

show	Show DHCP Server configuration.
list	List DHCP Server leases.
enable	Enable DHCP Server on a given interface.
disable	Disable DHCP Server on a given interface.
config	Configure the DHCP Server.

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
------------	--

### show

Synopsis:

```
nm dhcp-server show [-h]
```

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
------------	--

### list

Synopsis:

```
nm dhcp-server list [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

## enable

Synopsis:

```
nm dhcp-server enable [-h] {}
```

Detailed description of positional arguments:

```
{}
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

## disable

Synopsis:

```
nm dhcp-server disable [-h] {}
```

Detailed description of positional arguments:

```
{}
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

## config

Use this command to configure and activate DHCP Server on a single interface.

Synopsis:

```
nm dhcp-server config [-h] -r IP_RANGE [-l LEASE_TIME] [-d DNS]
                      [-g GATEWAY]
                      {}
```

Detailed description of positional arguments:

```
{}
```

Detailed description of named arguments:

```
-h, --help          show this help message and exit
-r IP_RANGE, --ip-range IP_RANGE
                  IP range - two IP addresses separated by '-' (eg
                  192.168.2.10-192.168.2.100).
-l LEASE_TIME, --lease-time LEASE_TIME
                  Lease time in seconds (default is 3600).
-d DNS, --dns DNS  DNS Server(s) to be provided to the client separated
                  by ',' (eg 8.8.8.8,1.1.1.1).
-g GATEWAY, --gateway GATEWAY
                  Gateway to be provided to the client (eg 192.168.2.1).
```

## 5.2 Device

This command has following subcommands:

serial_console	enable/disable control of EG via serial port
serial_get_config	get configuration of serial devices <b>and</b> stores it <b>in</b> a file
tpm_get	get registration_id <b>and</b> endorsement key <b>from</b> tpm
user_password_hash	get/ <b>set</b> user password hashes <b>from</b> /etc/shadow file
azure_set_config	<b>set</b> Azure configuration
azure_get_config	get Azure configuration <b>and</b> store <b>in</b> a file
azure_set_string	<b>set</b> Azure configuration to use provided connection string
azure_set_tpm	<b>set</b> Azure configuration to use provided scope <b>id</b> <b>and</b> registration id (TPM mode)
azure_set_dps_x509	<b>set</b> Azure configuration to use provided scope <b>id</b> , identity cert <b>and</b> identity pk
azure_set_certificate	Add certificates <b>for</b> IoT Edge
azure_configfile	Manage Azure IoT Edge config.
azure_set_option	<b>set</b> Azure option
motd_set	<b>set</b> message-of-the-day
motd_get	get message-of-the-day
issue_set	<b>set</b> message-of-the-day
issue_get	get message-of-the-day
get_config	get configuration <b>and</b> store <b>in</b> a file
set_config	sets configuration <b>and</b> store <b>in</b> a file
show	show configuration
oss	<b>print</b> open source software licenses
user	Add, remove <b>or</b> list system users
hostname	Set device hostname
erase	Remove data <b>from</b> persistent storage
logrotate	Change logrotation configuration
get_serialnumber	get serial number of the device
overcommit_memory	Change memory overcommit configuration.
set_local_console	enable/disable login via local console
get_local_console	check state of local linux console
sshauth	Manage ssh authentication methods <b>and</b> public keys
proxy	Set http/https proxy on system level ( <b>for</b> logged in users shells <b>and</b> for docker)
login_timeout	Set automatic logout after idle timeout.
localcertstore	Install certificate to local-device Trusted CA Store.
get_logs	Prepare archive <b>with</b> logs
smartems	Configure SmartEMS management service
certificate	Manage security certificate used by SmartEMS
swupdate	Perform software update
datetime	Configure date <b>and</b> time settings

### 5.2.1 serial\_console

By enabling/disabling the console output one can change if (and if yes on which) serial port system will print console output and allow the user to use it with help of serial terminal emulator. Configuration of console output will be exported to global configuration file. Those changes can be permanent or temporary (regarding state after re-boot). Hint: Enable or disable SysRq magic key functionality in the local\_console settings for syskeys management.

Synopsis:

device serial_console [-h] {} {now,at_boot,both} {on,off}
---

Detailed description of positional arguments:

```

{}           which serial device will be affected (if this is empty
            then the device is configured as not having serial
            devices or the configuration file is missing)
{now,at_boot,both} if new state shall be immediate and/or applied also
                  after reboot
{on,off}        turn the console on or off on selected device

```

Detailed description of named arguments:

```
-h, --help      show this help message and exit
```

Examples:

after next (and later) reboots console will be active on serial port 1, current state will not be affected

```
device serial_console 1 at_boot on
```

turn off console on serial port 0 immediately and keep it that way after reboot

```
device serial_console 0 both off
```

turn on console at serial port 1 immediately, state after reboot will not be affected

```
device serial_console 1 now on
```

## 5.2.2 serial\_get\_config

Gets configuration of serial ports and store it in a file `serial_config.json` (e.g. for backup purposes).

Synopsis:

```
device serial_get_config [-h]
```

Detailed description of named arguments:

```
-h, --help      show this help message and exit
```

Examples:

save serial config to file `serial_config.json` and print it to the screen

```
device serial_get_config ; cat ./serial_config.json
```

## 5.2.3 tpm\_get

This function will get the endorsement key and registration id from built-in TPM module and print it out. Those keys can be used to provide provisioning configuration for Azure IoT Edge daemon. Note that TPM module may respond slowly.

Synopsis:

```
device tpm_get [-h]
```

Detailed description of named arguments:

```
-h, --help      show this help message and exit
```

Examples:

the only way to call this command

```
device tpm_get
```

## 5.2.4 user\_password\_hash

This command will get the users and their password hashes from /etc/shadow file and print it out or set a new ones provided in a config file.

This command has following subcommands:

show	get user password hashes <b>from</b> /etc/shadow file
set_config	<b>set</b> user password hashes to /etc/shadow file

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
------------	--

Examples:

```
device user_password_hash
```

### show

Synopsis:

device user_password_hash show [-h]
-------------------------------------

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
------------	--

### set\_config

Synopsis:

device user_password_hash set_config [-h] [-f FILENAME]
---

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
-f FILENAME, --filename FILENAME	path to a config file

## 5.2.5 azure\_set\_config

Restore Azure IoT Edge daemon configuration from a file. This is a permanent change (and will overwrite existing Azure configuration.)

Synopsis:

device azure_set_config [-h] [-f FILENAME]
--

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
-f FILENAME, --filename FILENAME	file <b>with</b> configuration data (default is 'azure_config.json')

Examples:

restore config from file `azure_config.json`

```
device azure_set_config azure_config.json
```

Example content of config file:

```
{
  "azure": {
    "source": "manual",
    "device_connection_string": "connectionString",
    "hostname": "<ADD HOSTNAME HERE>"
  }
}
```

## 5.2.6 `azure_get_config`

Azure configuration (provisioning data) will be saved to json file named `azure_config.json`.

Synopsis:

```
device azure_get_config [-h] [--export-private-keys]
```

Detailed description of named arguments:

<code>-h, --help</code>	show this help message <b>and</b> exit
<code>--export-private-keys</code>	

Examples:

the only way to call this command

```
device azure_get_config
```

## 5.2.7 `azure_set_string`

Configures Azure IoT Edge daemon to use connection string as a manual provisioning. Remember to use quotation marks for provided string (see examples).

Synopsis:

```
device azure_set_string [-h] connection_string
```

Detailed description of positional arguments:

<code>connection_string</code>	connection string to be used
--------------------------------	------------------------------

Detailed description of named arguments:

<code>-h, --help</code>	show this help message <b>and</b> exit
-------------------------	--

Examples:

set connection string value to Connection String

```
device azure_set_string 'Connection String'
```

## 5.2.8 azure\_set\_tpm

Configures Azure IoT Edge daemon to use TPM module for provisioning. This change is permanent (performing configuration backup is up to the user)

Synopsis:

```
device azure_set_tpm [-h] id_scope registration_id
```

Detailed description of positional arguments:

id_scope	ID scope <b>from DPS</b>
registration_id	registration ID <b>from TPM</b> of the device

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
------------	--

Examples:

note that registrationIDFromTPMModule is device specific and can be obtained with command device tpm\_get

```
device azure_set_tpm scopeIDFromIoTHub registrationIDFromTPMModule
```

## 5.2.9 azure\_set\_dps\_x509

Configures Azure IoT Edge daemon to use X.509 certificates provisioning method. Three arguments are needed for configuration: id scope from IoT Hub, certificate file and private key file. You need read permissions for these files. This change is permanent (performing configuration backup is up to the user)

Synopsis:

```
device azure_set_dps_x509 [-h] -k IDENTITY_PK -p IDENTITY_CERT -i
                           ID_SCOPE
```

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
-k IDENTITY_PK, --identity_pk IDENTITY_PK	
-p IDENTITY_CERT, --identity_cert IDENTITY_CERT	
-i ID_SCOPE, --id_scope ID_SCOPE	

Examples:

```
device azure_set_dps_x509 -i scope_id_from_iot_hub -p /path/to/cert_file -k /path/to/private_key_
                           file
```

## 5.2.10 azure\_set\_certificate

Configures Azure IoT Edge daemon to use provided certificates. Device private key and device CA certificate will be used by device to prove its own identity. Device certificate needs to be signed by trust bundle certificate specific for IoT Edge scenario — public part of this trust bundle certificate is required on each device participating in the scenario too. Note that anyone knowing private key for device CA cert can impersonate this device in given IoT edge scenario

Synopsis:

```
device azure_set_certificate [-h] -t TRUST_BUNDLE_CERT -d
                           DEVICE_CA_CERT -p DEVICE_CA_PK
```

Detailed description of named arguments:

```
-h, --help          show this help message and exit
-t TRUST_BUNDLE_CERT, --trust_bundle_cert TRUST_BUNDLE_CERT
-d DEVICE_CA_CERT, --device_ca_cert DEVICE_CA_CERT
-p DEVICE_CA_PK, --device_ca_pk DEVICE_CA_PK
```

Examples:

all 3 files must be readable for you

```
device azure_set_certificate -t path/to/trust_bundle_cert -d path/to/device_ca_cert -p path/to/
device_ca_private_key
```

## 5.2.11 azure\_configfile

Get full Azure IoT Edge configuration in toml file or upload preconfigured file. Notice: Exported file contains all settings, but some of them are ignored during import (see the details in description of import)

This command has following subcommands:

export	Get toml <b>with</b> Azure configuration. All entries which are <b>set in</b> Azure config file are present, so user can use <b>for</b> analysis <b>or</b> to test it outside of Edge Gateway
<b>import</b>	<b>Set</b> Azure config based on given toml file.

Detailed description of named arguments:

```
-h, --help          show this help message and exit
```

Examples:

```
device azure_configfile
```

### export

Synopsis:

```
device azure_configfile export [-h] [-f FILENAME]
```

Detailed description of named arguments:

```
-h, --help          show this help message and exit
-f FILENAME, --filename FILENAME
                  file to write to (default is 'iotedge.toml')
```

### import

This method is designed to allow import of Azure config prepared on machine other than Edge Gateway, therefore parameters which are handled specially for Edge Gateway will be ignored. This affects especially hostname and certificates, but also some paths which shall not be modified. Response to this command will inform user if any entries were ignored. To see exactly what was ignored you can run export and compare your input file with reexported contents. If you want to export/import whole Azure configuration between Edge Gateways in simpler way use azure\_get\_config/azure\_set\_config commands instead of azure\_configfile export/import.

Synopsis:

```
device azure_configfile import [-h] -f FILENAME
```

Detailed description of named arguments:

<code>-h, --help</code>	show this help message <b>and</b> exit
<code>-f FILENAME, --filename FILENAME</code>	

## 5.2.12 `azure_set_option`

Change selected entry in IoT Edge TOML config. This option takes a string as a `topic` parameter which indicates topic-key in TOML tree to be changed. If selected topic-key does not exist system will create it in config file but if it does exist this command will change its value to the one specified in `entry` parameter. The `entry` parameter can be used more than once. When `topic` is not given entries are treated as global key-value pairs. This command does not verify if topic-key name and entry is reasonable and understood by Azure, but some options are protected and cannot be changed this way if it would not make sense in Edge Gateway (for example certificate paths are predefined for Edge Gateways, instead of changing those paths in Azure config you shall use `azure_set_certificate` command).

Synopsis:

<code>device azure_set_option [-h] [-t TOPIC] -e ENTRY [-d]</code>
--

Detailed description of named arguments:

<code>-h, --help</code>	show this help message <b>and</b> exit
<code>-t TOPIC, --topic TOPIC</code>	topic to setup
<code>-e ENTRY, --entry ENTRY</code>	entry being key-value pair to be <b>set</b> , note that TOML will NOT interpret its <code>type</code> . You need to use proper quotation <b>as in</b> examples above.
<code>-d, --dry_run</code>	Do <b>not set</b> option, but show partial TOML which would be added to config

Examples:

change attestation method to tpm

<code>device azure_set_option -t provisioning.attestation -e 'method = "tpm"</code>
---

show partial TOML to add topic f.b.z with value being list of two strings

<code>device azure_set_option -t f.b.z -e 'l = ["a", "1"]' -d</code>
--

show partial TOML to add topic f.b.z with value being list of a string and a number

<code>device azure_set_option -t f.b.z -e 'l = ["a", 1]' -d</code>
--

add topic f.b.z with two entries

<code>device azure_set_option -t f.b.z -e 'x = "a"' -e 'y = "b"'</code>
---

## 5.2.13 motd\_set

set new welcome-banner (MotD), shown after logging in

Synopsis:

```
device motd_set [-h] (-f FILE | -t TEXT)
```

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
-f FILE, --file FILE	set new MotD <b>from</b> file
-t TEXT, --text TEXT	set new MotD <b>from</b> plain-text

## 5.2.14 motd\_get

get current welcome-banner (MotD), shown after logging in

Synopsis:

```
device motd_get [-h]
```

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
------------	--

## 5.2.15 issue\_set

set new banner, shown before logging in

Synopsis:

```
device issue_set [-h] (-f FILE | -t TEXT)
```

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
-f FILE, --file FILE	set new banner <b>from</b> file
-t TEXT, --text TEXT	set new banner <b>from</b> plain-text

## 5.2.16 issue\_get

get current banner, shown before logging in

Synopsis:

```
device issue_get [-h]
```

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
------------	--

## 5.2.17 get\_config

Whole device configuration will be saved to json file named `device_config.json`.

Synopsis:

```
device get_config [-h] [--export-private-keys]
```

Detailed description of named arguments:

<code>-h, --help</code>	show this help message <b>and</b> exit
<code>--export-private-keys</code>	Governs export of private keys <b>and</b> user password hashes

Examples:

the only way to call this command

```
device get_config
```

## 5.2.18 set\_config

Whole device configuration will be restored from a file.

Synopsis:

```
device set_config [-h] [-f FILENAME] [--unconditionally]
```

Detailed description of named arguments:

<code>-h, --help</code>	show this help message <b>and</b> exit
<code>-f FILENAME, --filename FILENAME</code>	file <b>with</b> configuration data (default is ' <code>device_config.json</code> ')
<code>--unconditionally</code>	Prevent connectivity checking after executing this command (without this option user may be asked to confirm that after command execution he has <b>not</b> lost connection to the device, without such confirmation command would be rolled back.)

Examples:

restore config from file `device_config.json`

```
device set_config --filename device_config.json
```

Example JSON file:

```
{
  "azure": {
    "source": "manual",
    "device_connection_string": "<ADD DEVICE CONNECTION STRING HERE>",
    "hostname": "<ADD HOSTNAME HERE>"
  },
  "serial": {
    "serial0": {
      "console_output": {
        "at_startup": true,
        "currently": true
      }
    }
  }
}
```

(continues on next page)

(continued from previous page)

```

  },
  "serial1": {
    "console_output": {
      "at_startup": false,
      "currently": false
    }
  },
  "network": {
    "lan2": {
      "dhcp": true,
      "ignore_default_route": false,
      "current_ip": "192.168.1.95",
      "current_subnet": "24",
      "current_gateway": "192.168.1.1",
      "current_dns": "1.1.1.1"
    },
    "lan1": {
      "dhcp": false,
      "ip": [
        "192.168.2.1"
      ],
      "subnet": [
        "24"
      ],
      "gateway": null,
      "dns": null,
      "current_ip": "192.168.2.1",
      "current_subnet": "24",
      "current_gateway": null,
      "current_dns": null
    }
  },
  "static_routing": {
    "enabled": false,
    "selected": "disabled",
    "saved": {
      "disabled": {}
    },
    "edited": {}
  },
  "firewall": {
    "enabled": false,
    "selected": "allow_all",
    "edited": {},
    "saved": {
      "allow_all": {
        "inet": {
          "filter": {
            "output": {
              "policy": "accept"
            },
            "input": {
              "policy": "accept"
            },
            "forward": {
              "policy": "accept"
            }
          }
        }
      }
    }
  }
}

```

(continues on next page)

(continued from previous page)

```

  },
  "ip": {
    "nat": {
      "postrouting": {
        "policy": "accept"
      },
      "prerouting": {
        "policy": "accept"
      }
    }
  },
  "notes": "This is the minimum configuration of firewall. This preset cannot be modified or removed.\n\nThis configuration does not drop or alter any packets."
},
"disabled": {
  "inet": {
    "filter": {
      "output": {
        "policy": "accept"
      },
      "input": {
        "policy": "accept"
      },
      "forward": {
        "policy": "accept"
      }
    }
  },
  "ip": {
    "nat": {
      "postrouting": {
        "policy": "accept"
      },
      "prerouting": {
        "policy": "accept"
      }
    }
  },
  "notes": "This preset disables firewall. This preset cannot be modified or removed.\n\nThere is special closure/disable part in this preset which totally flushes out\nfirewall\n\ntables. Effect is very similar to allow all, but conceptually the\ndifference is that here we\n\nensure that firewall is really doing nothing\n(theoretically allow all could be doing actions\n\nlike categorizing and counting\npackets).",
    "closure": {
      "disable": {
        "contents": "flush ruleset",
        "notes": "Removes all rules from firewall"
      }
    }
  },
  "ovpn": {}
}

```

## 5.2.19 Set datetime using date binary

It is possible to set a system time in the device locally using 'date' command. Please note that Edge Gateway is configured with NTP enabled in factory default which will overwrite manually set datetime values.

```

Usage: date [OPTION]... [+FORMAT]
  or: date [-u|--utc|--universal] [MMDDhhmm[[CC]YY][.ss]]
Display date and time in the given FORMAT.
With -s, or with [MMDDhhmm[[CC]YY][.ss]], set the date and time.
Mandatory arguments to long options are mandatory for short options too.
-d, --date=STRING           display time described by STRING, not 'now'
--debug                      annotate the parsed date,
                             and warn about questionable usage to stderr
-f, --file=DATEFILE         like --date; once for each line of DATEFILE
-I[FMT], --iso-8601[=FMT]   output date/time in ISO 8601 format.
                           FMT='date' for date only (the default),
                           'hours', 'minutes', 'seconds', or 'ns'
                           for date and time to the indicated precision.
                           Example: 2006-08-14T02:34:56-06:00
--resolution                output the available resolution of timestamps
                           Example: 0.000000001
-R, --rfc-email             output date and time in RFC 5322 format.
                           Example: Mon, 14 Aug 2006 02:34:56 -0600
--rfc-3339=FMT              output date/time in RFC 3339 format.
                           FMT='date', 'seconds', or 'ns'
                           for date and time to the indicated precision.
                           Example: 2006-08-14 02:34:56-06:00
-r, --reference=FILE        display the last modification time of FILE
-s, --set=STRING             set time described by STRING
-u, --utc, --universal      print or set Coordinated Universal Time (UTC)
--help                      display this help and exit
--version                   output version information and exit

```

Example usage:

```
date -s '1984-01-04 09:33:00'
```

## 5.2.20 show

Whole device configuration will be printed out. Note that this is quite verbose.

Synopsis:

```
device show [-h] [--export-private-keys]
```

Detailed description of named arguments:

```

-h, --help                  show this help message and exit
--export-private-keys

```

Examples:

the only way to call this command

```
device show
```

## 5.2.21 oss

Retrieves information about installed packages and their licenses.

Synopsis:

```
device oss [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

Examples:

the only way to call this command

```
device oss
```

## 5.2.22 user

Add, remove or list system users. User home directories are created automatically with paths specific for the group of a user. For the `user` group account path to home is `/home/ro_users/{usrnm}` where `{usrnm}` is the username. For the `admin` group account path to home is `/home/admins/{admnm}` where `{admnm}` is the username.

This command has following subcommands:

<code>add</code>	Add system users
<code>remove</code>	Remove system users
<code>list</code>	List system users

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

Examples:

adds read only user `user_ro` with password 12345

```
device user add -g user -p 12345 -u user_ro
```

adds admin user

```
device user add -g admin -p 12345 -u admin
```

remove user but leave his home directory on disk

```
device user remove -u user_ro
```

remove user and all of his home files

```
device user remove -u admin -d
```

## add

Synopsis:

```
device user add [-h] -u USERNAME -g {admin,user} -p PASSWORD
```

Detailed description of named arguments:

<code>-h, --help</code>	show this help message and exit
<code>-u USERNAME, --username USERNAME</code>	Login name (which is a unique identifier in the system) of a user to be added.
<code>-g {admin,user}, --group {admin,user}</code>	Group of a user determines permissions in the system and is mandatory when adding new user. Users of group `admin` have full access configuration management, users of group `user` can only execute commands which do not change configuration. To choose account group, available options are `user` with read only access to CLI and `admin` with full access to CLI.
<code>-p PASSWORD, --password PASSWORD</code>	Password is mandatory when adding user.

## remove

Synopsis:

```
device user remove [-h] -u USERNAME [-d]
```

Detailed description of named arguments:

<code>-h, --help</code>	show this help message and exit
<code>-u USERNAME, --username USERNAME</code>	Login name (which is a unique identifier in the system) of a user to be removed.
<code>-d, --deletehome</code>	Causes user home directory and its contents to be deleted.

## list

Synopsis:

```
device user list [-h]
```

Detailed description of named arguments:

<code>-h, --help</code>	show this help message and exit
-------------------------	---------------------------------

## 5.2.23 hostname

Sets device hostname, this will also set hostname in IoT Edge daemon config. Note that it may break Azure configuration which could be depending on that name.

Synopsis:

```
device hostname [-h] name
```

Detailed description of positional arguments:

```
name
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

Examples:

change own hostname to eg210 and check that it can be pinged

```
device hostname eg210; ping -c 1 eg210
```

## 5.2.24 erase

Allows to perform full factory reset of device. All files created after installation (including user files, dockers and config for services) will be removed.

Synopsis:

```
device erase [-h] {everything}
```

Detailed description of positional arguments:

```
{everything}  what to erase
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

Examples:

perform factory reset

```
device erase everything
```

## 5.2.25 logrotate

Changes when log files will be renamed and removed

This command has following subcommands:

<code>set</code>	Change config for logrotate service
<code>show</code>	Show current config

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

Examples:

new log file will be created after current grows above 100MB or new day starts, keep only last 7 log files on disk

```
device logrotate set --size 100 --rotate 7 --period daily
```

display current logrotate configuration

```
device logrotate show
```

## set

Synopsis:

```
device logrotate set [-h] -p {hourly,daily,weekly,monthly} -r ROTATE -s
                     SIZE
```

Detailed description of named arguments:

```
-h, --help      show this help message and exit
-p {hourly,daily,weekly,monthly}, --period {hourly,daily,weekly,monthly}
           How often log files are rotated.
-r ROTATE, --rotate ROTATE
           Logrotate rotates the log files that many times before
           removal. If it's set to 0, old versions are removed
           rather than rotated.
-s SIZE, --size SIZE Maximum size of the log file in megabytes. Logrotate
           rotates the log at selected period, but when the log
           file reaches it's maximum size, logrotate rotates log
           despite the period.
```

## show

Synopsis:

```
device logrotate show [-h]
```

Detailed description of named arguments:

```
-h, --help      show this help message and exit
```

## 5.2.26 get\_serialnumber

Serial number of the device will be printed out.

Synopsis:

```
device get_serialnumber [-h]
```

Detailed description of named arguments:

```
-h, --help      show this help message and exit
```

Examples:

the only way to call this command

```
device get_serialnumber
```

## 5.2.27 overcommit\_memory

This enables or disables overcommitting of the memory. When disabled, the machine will not run programs that would exceed available memory. When enabled, OOM killer might kill programs that it finds suitable to kill.

Synopsis:

```
device overcommit_memory [-h] {enable,disable,default,status}
```

Detailed description of positional arguments:

```
{enable,disable,default,status}
```

Detailed description of named arguments:

```
-h, --help      show this help message and exit
```

Examples:

```
device overcommit_memory enable
device overcommit_memory disable
device overcommit_memory status
device overcommit_memory default
```

## 5.2.28 set\_local\_console

This enables or disables linux local console (TTY) \*\*\* IMPORTANT - this command, might lock you out.

Synopsis:

```
device set_local_console [-h] [-l {enable,disable}]
                           [-s {enable,disable}]
```

Detailed description of named arguments:

```
-h, --help      show this help message and exit
-l {enable,disable}, --login {enable,disable}
               Enable or disable linux local login
-s {enable,disable}, --syskeys {enable,disable}
               Enable or disable Ctrl-Alt-Del, SysRq keys action.
               This option enables or disables SysRq to both
               consoles: serial (COM1) and local (TTY)
```

## 5.2.29 get\_local\_console

Synopsis:

```
device get_local_console [-h]
```

Detailed description of named arguments:

```
-h, --help      show this help message and exit
```

## 5.2.30 sshauth

Allows to manage if password and public key based authentication is available for ssh connectitons. At least one method must be allowed. If password based authentication is going to be turned off, then at least admin account must have at least one valid public key present in “~/.ssh/authorized\_keys”.

This command has following subcommands:

set_config	Replace ssh config and user keys with new values
get_config	Return current ssh config
set	Change allowed types of ssh authentication
show	Show current ssh authentication configuration
list_publickeys	Display content of ~/.ssh/authorized_keys for currently logged in user
add_publickey	Adds a public key from a keypair for selected user to

(continues on next page)

(continued from previous page)

	authorized_keys. If you want to update comment to already existing key first you have removed it <b>with</b> <b>remove_key</b> option.
<b>remove_key</b>	Remove key <b>with</b> given index <b>for</b> currently logged in user
<b>maxsessions</b>	Specifies the maximum number of <b>open</b> shell, login or subsystem (e.g. sftp) sessions permitted per network connection.
<b>maxstartups</b>	Specifies the maximum number of concurrent unauthenticated connections to the SSH daemon.

Detailed description of named arguments:

<b>-h, --help</b>	show this help message <b>and</b> exit
-------------------	--

Examples:

allow key based authentication but disable password based one

device sshauth set --public_key_auth on --password_auth off
---

disable password auth (leave key based auth in same state as it was before — this command will fail if key based authentication was turned off already)

device sshauth set -p off
---------------------------

display current ssh authentication configuration

device sshauth show
---------------------

## set\_config

This will first validate that at least one authentication method is enabled in incoming config, if yes then proceed to replace users ssh public keys. In case of failure for any user, allowed authentication methods will be set as requested but password based authentication will be enabled always in case admin user authorized\_keys will be empty, to prevent total lock out from device. Keys of users not listed in the json will not be modified — to remove keys of users they need to be present in json file with empty list of keys. Warning: in case of issues with keys in json file it may cause state where some users have changed keys, and some user have old keys — please analyze failures of this command carefully.

Synopsis:

device sshauth set_config [-h] [-f FILENAME]
--

Detailed description of named arguments:

<b>-h, --help</b>	show this help message <b>and</b> exit
<b>-f FILENAME, --filename FILENAME</b>	file <b>with</b> configuration data (default <b>is</b> <b>'ssh_config.json'</b> )

## get\_config

Synopsis:

```
device sshauth get_config [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

## set

Synopsis:

```
device sshauth set [-h] [-k {on,off}] [-p {on,off}]
```

Detailed description of named arguments:

```
-h, --help      show this help message and exit
-k {on,off}, --public_key_auth {on,off}
-p {on,off}, --password_auth {on,off}
```

## show

Synopsis:

```
device sshauth show [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

## list\_publickeys

Synopsis:

```
device sshauth list_publickeys [-h] [-u USERNAME]
```

Detailed description of named arguments:

```
-h, --help      show this help message and exit
-u USERNAME, --username USERNAME
```

## add\_publickey

Synopsis:

```
device sshauth add_publickey [-h] -f FILENAME [-u USERNAME]
```

Detailed description of named arguments:

```
-h, --help      show this help message and exit
-f FILENAME, --filename FILENAME
-u USERNAME, --username USERNAME
```

## remove\_key

Synopsis:

```
device sshauth remove_key [-h] -i INDEX [-u USERNAME]
```

Detailed description of named arguments:

```
-h, --help      show this help message and exit
-i INDEX, --index INDEX
-u USERNAME, --username USERNAME
```

## maxsessions

Synopsis:

```
device sshauth maxsessions [-h] sessions
```

Detailed description of positional arguments:

```
sessions
```

Detailed description of named arguments:

```
-h, --help      show this help message and exit
```

## maxstartups

Synopsis:

```
device sshauth maxstartups [-h] startups
```

Detailed description of positional arguments:

```
startups
```

Detailed description of named arguments:

```
-h, --help      show this help message and exit
```

## 5.2.31 proxy

This command has following subcommands:

add	Add or overwrite proxy or proxies
del	Delete proxies
set_config	Replace proxy config with new one
get_config	Return current proxy config (except for docker-compose)

Detailed description of named arguments:

```
-h, --help      show this help message and exit
```

## add

You may give http and/or https proxy parameters. This command will add them (or overwrite if any is already configured) for azure daemons, docker and shell environment as well as for docker-compose (Note: docker-compose stores its proxy settings in separate physical location and this forces docker- compose proxy to be kept in separate subsection of EG global json config). If you give proxy only for one protocol (http/https) and the other is already configured, this other will not be removed. For individual users' environments, logging in again is needed to notice configuration change. Immediately after storing new proxy in the configurations response will be sent back to the user and daemons which use proxy (docker and containers) will be restarted. This restart of deamons can take considerable amount of time (and potentially disrupt processing done by containers).

Synopsis:

```
device proxy add [-h] [-p HTTP] [-s HTTPS] [-n]
```

Detailed description of named arguments:

<code>-h, --help</code>	show this help message and exit
<code>-p HTTP, --http HTTP</code>	set HTTP-Proxy to <code>http://&lt;SERVER&gt;:&lt;PORT&gt;</code> (e.g. <code>http://192.168.123.254:8080</code> )
<code>-s HTTPS, --https HTTPS</code>	set HTTPS-Proxy to <code>https://&lt;SERVER&gt;:&lt;PORT&gt;</code> (e.g. <code>https://192.168.123.254:8080</code> )
<code>-n, --no_reload</code>	Change configuration, but do not reload it immediately in all daemons. If you give this option new proxy will be used by docker containers after next reboot of the system or next restart of docker subsystem (whichever comes first). To manually enforce restart of docker execute command <code>`docker-config apply`</code> .

## del

Delete http and/or https proxies

Synopsis:

```
device proxy del [-h] [--http] [--https]
```

Detailed description of named arguments:

<code>-h, --help</code>	show this help message and exit
<code>--http</code>	delete http proxy
<code>--https</code>	delete https proxy

## set\_config

This will add/remove system and docker daemon proxies to match contents of given config. This will not change docker-compose proxy settings! Docker and containers will be restarted according to boolean entry 'reload\_daemons' which can optionally be present next to the object proxy\_servers in json file used with this command. If that entry is missing its value is assumed to be true.

Synopsis:

```
device proxy set_config [-h] [-f FILENAME]
```

Detailed description of named arguments:

<code>-h, --help</code>	show this help message and exit
<code>-f FILENAME, --filename FILENAME</code>	file with configuration data (default is <code>'proxy_config.json'</code> )

## get\_config

This will return partial EG config for proxy only. Note that because docker- compose stores its proxy settings in separate place you would need to use command `docker-config compose get-config` to get partial config containing proxy of docker-compose.

Synopsis:

```
device proxy get_config [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

## 5.2.32 login\_timeout

This will set a system-wide auto-logout policy. Every user, after N-seconds of idle will be logged off.

This command has following subcommands:

<code>set</code>	Set the value <b>for</b> automatic idle logout
<code>get</code>	Get the value <b>for</b> automatic idle logout

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

### set

Configure every user login to be closed after idle time

Synopsis:

```
device login_timeout set [-h] -s SECONDS
```

Detailed description of named arguments:

<code>-h, --help</code>	show this help message and exit
<code>-s SECONDS, --seconds SECONDS</code>	Amount of idle seconds <b>for</b> automatic logout (0 means infinity, values 1 to 9 are rejected)

### get

Read All-Users default idle logout time

Synopsis:

```
device login_timeout get [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

## 5.2.33 localcertstore

This command has following subcommands:

```
install  Install new CRT
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

### install

Synopsis:

```
device localcertstore install [-h] -f FILE
```

Detailed description of named arguments:

```
-h, --help      show this help message and exit
-f FILE, --file FILE  Path to CRT file
```

## 5.2.34 get\_logs

Prepares archive logs.zip with currently existing logs.

Synopsis:

```
device get_logs [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

Examples:

the only way to call this command

```
device get_logs
```

## 5.2.35 smartems

This command has following subcommands:

config	Change config for auto update service
set_config	Replace current Smart EMS configuration
show	Show current config
check	Trigger immediate check for new Smart EMS management commands

Detailed description of named arguments:

```
-h, --help      show this help message and exit
```

Examples:

display current configuration

```
device smartems show
```

immediately connect to SmartEMS to check for any management commands

```
device smartems check
```

Other examples:

```
device smartems config --username user --password pass --url url
device smartems config --username user --password pass --url url --vcc_api_endpoint
```

## config

Synopsis:

```
device smartems config [-h] -u USERNAME -p PASSWORD -U URL [-s]
[-i INTERVAL] [--vcc_api_endpoint]
```

Detailed description of named arguments:

```
-h, --help          show this help message and exit
-u USERNAME, --username USERNAME
                  Username for Smart EMS
-p PASSWORD, --password PASSWORD
                  Password for Smart EMS
-U URL, --url URL
                  URL for Smart EMS
-s, --skip          Skip checking SSL certificate for Smart EMS.DANGER!
                  This allows man-in-the-middle attacks.
-i INTERVAL, --interval INTERVAL
                  Period between two checks, in seconds. The minimum is
                  10s.
--vcc_api_endpoint If present, this API endpoint will be set -
                  /api/edgegatewayvcc/configuration. Otherwise, this one
                  will be used - /api/edgegateway/configuration. If your
                  EdgeGateway is connected to VPN CC use this option.
```

## set\_config

Synopsis:

```
device smartems set_config [-h] [-f FILENAME]
```

Detailed description of named arguments:

```
-h, --help          show this help message and exit
-f FILENAME, --filename FILENAME
                  file with configuration data (default is
                  'smart_ems.json')
```

## show

Synopsis:

```
device smartems show [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

## check

This command will trigger an immediate connection to the SmartEMS and perform any updates requested by SmartEMS (it may be config and or software update) or provide information requested by SmartEMS (like current configuration). If software update is requested then EG will download package first — depending on connection speed this may consume bigger amount of time. This command times out after five minutes but even in such case download is still being performed in the background. The new firmware package is being stored in /tmp and has .swu extension, so you can check in that directory if it is growing. After firmware is downloaded it will be automatically installed and system will reboot.

Synopsis:

```
device smartems check [-h]
```

Detailed description of named arguments:

```
-h, --help show this help message and exit
```

## 5.2.36 certificate

This command has following subcommands:

add	Add new certificate
delete	Remove current certificate
show	Display current certificate

Detailed description of named arguments:

```
-h, --help show this help message and exit
```

### add

Synopsis:

```
device certificate add [-h] -c CERTIFICATE
```

Detailed description of named arguments:

```
-h, --help show this help message and exit
-c CERTIFICATE, --certificate CERTIFICATE
        Filename with certificate
```

### delete

Synopsis:

```
device certificate delete [-h]
```

Detailed description of named arguments:

```
-h, --help show this help message and exit
```

## show

Synopsis:

```
device certificate show [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

## 5.2.37 swupdate

Synopsis:

```
device swupdate [-h] -f FILENAME
```

Detailed description of named arguments:

```
-h, --help      show this help message and exit
-f FILENAME, --filename FILENAME
          SWU file
```

Examples:

perform software update with selected .swu file

```
device swupdate -f/--filename
```

## 5.2.38 datetime

This command has following subcommands:

set_config	Replace ntp config <b>with</b> new one
get_config	Return current ntp <b>and</b> timezone config
show	Show current datetime status
set_ntp	Change NTP configuration
enable	Enable NTP service
disable	Enable NTP service
list_timezones	List <b>all</b> avaible timezones
set_timezone	List <b>all</b> avaible timezones

Detailed description of named arguments:

```
-h, --help      show this help message and exit
```

Examples:

display current NTP status

```
device datetime show
```

enable NTP service

```
device datetime enable
```

disable NTP service

```
device datetime disable
```

list supported timezones

```
device datetime list_timezones
```

set timezone to Berlin time

```
device datetime set_timezone Europe/Berlin
```

set NTP to use provided servers

```
device datetime set_ntp --server "time1.ntp time2.ntp"
```

set primary and fallback servers for NTP

```
device datetime set_ntp --server "time1.ntp time2.ntp" --fallback- servers "time3.ntp time4.ntp"
```

set minimum and maximum intervals (in seconds) between two synchronization events

```
device datetime set_ntp --server time1.ntp --interval-minimum 16 --interval-maximum 32
```

## set\_config

This will set configuration of ntp and select timezone.

Synopsis:

```
device datetime set_config [-h] [-f FILENAME]
```

Detailed description of named arguments:

```
-h, --help      show this help message and exit
-f FILENAME, --filename FILENAME
               file with configuration data (default is
               'datetime_config.json')
```

## get\_config

Synopsis:

```
device datetime get_config [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

## show

Synopsis:

```
device datetime show [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

## set\_ntp

Synopsis:

```
device datetime set_ntp [-h] -s SERVER [-f FALBACK_SERVERS]
[-i INTERVAL_MINIMUM] [-I INTERVAL_MAXIMUM]
```

Detailed description of named arguments:

```
-h, --help      show this help message and exit
-s SERVER, --server SERVER
  IP address or hostname for main NTP servers, this
  parameter accept multiple servers separated by spaces.
  If multiple servers are provided they have to be
  enclosed within quotation marks
-f FALBACK_SERVERS, --fallback-servers FALBACK_SERVERS
  IP address or hostname for fallback server, this
  parameter accepts multiple servers separated by spaces.
  Those servers will be used to synchronize time when
  main NTP server is inaccessible. Defaults to:
  time1.google.com time2.google.com time3.google.com
  time4.google.com. If multiple servers provided they
  have to be enclosed with quotation mark.
-i INTERVAL_MINIMUM, --interval-minimum INTERVAL_MINIMUM
  Minimum time in seconds between two NTP messages.
  Defaults to 32 Minimum value is 16, maximum value is
  2048. Minimum value can not be greater than maximum
  interval.
-I INTERVAL_MAXIMUM, --interval-maximum INTERVAL_MAXIMUM
  Maximum time in seconds between two NTP messages.
  Defaults to 2048. Minimum value is 16, maximum value
  is 2048. Maximum time can not be lesser than minimum
  time.
```

## enable

Synopsis:

```
device datetime enable [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

## disable

Synopsis:

```
device datetime disable [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

## list\_timezones

Synopsis:

```
device datetime list_timezones [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

## set\_timezone

Synopsis:

```
device datetime set_timezone [-h] {}
```

Detailed description of positional arguments:

```
{}      Set timezone
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

## 5.3 Firewall

This command has following subcommands:

default	select and enable default firewall config (based on preset default)
enable	enable firewall using configuration selected earlier by preset_select or set_config
disable	disables firewall
set_config	restore firewall configuration from a json file
get_config	get configuration to firewall_config.json file
show	show firewall configuration in terse way
commit	affirm that current state of firewall is correct, '(prevents rollback of yet uncommitted actions)
cleanup	remove traces of uncommitted transaction without touching rest of the config
reload	reload configuration from scratch, as would be done after reboot
preset	Manage firewall preset states (e.g. mark preset as being edited)
modify	Modify preset in being edited state
print	print contents of preset being edited (whole or just a part)

Unrelated commands examples:

```
fw default
fw enable
fw disable
fw set_config --filename firewall.config
fw get_config
fw preset_create my_new_preset -s allow_all
fw modify set_policy -r -p inet drop
```

(continues on next page)

(continued from previous page)

```

fw modify set_policy -p inet/filter/output accept
fw print
fw modify erase -p inet/filter/common/mgmtd/cli_allow_null_22
fw modify erase -p inet/filter/input/mgmtd/cli_allow_lan1_23
  
```

Multicommand example in which we create new preset (based on default one) with rule that presents virtual IP 192.168.2.202 visible on the lan1 side which is redirected to hidden private IP 192.168.1.102. We also disable any forwarding except the connections originating from the hidden private IP (for such connections traffic in both ways will be accepted thanks to preexisting connection tracking rule in default preset — we know about that rule because we have printed preset just after creating it). After we add our new rules we again print the modified part, then save, select and enable our preset:

```

fw preset create virt_ip_on_lan1 -s default
fw print
fw modify nat_n_on_n add from_lan1to2 --public_interface lan1 --ip_public 192.168.2.202 --ip_private 192.168.1.102
fw modify set_policy -p inet/filter/forward drop
fw modify forward -s 192.168.1.102 -v accept
fw print -p ip
fw preset save
fw preset select virt_ip_on_lan1
fw enable
  
```

### 5.3.1 default

Select a default preset (currently allow\_management) and enables it All firewall rules that are currently set will be cleared. Also, the firewall will be enabled and set to automatically start on boot.

Synopsis:

```
fw default [-h] [--unconditionally]
```

Detailed description of named arguments:

<code>-h, --help</code>	show this help message <b>and</b> exit
<code>--unconditionally</code>	Prevent connectivity checking after executing this command (without this option user may be asked to confirm that after command execution he has <b>not</b> lost connection to the device, without such confirmation command would be rolled back.)

Examples:

the only way to call this command

```
fw default
```

### 5.3.2 enable

Loads firewall rules into the kernel immediately and after reboot. Before enabling firewall a preset must be selected (default preset is selected initially after factory reset).

Synopsis:

```
fw enable [-h] [--unconditionally]
```

Detailed description of named arguments:

```

-h, --help      show this help message and exit
--unconditionally  Prevent connectivity checking after executing this
                  command (without this option user may be asked to confirm
                  that after command execution he has not lost connection
                  to the device, without such confirmation command would be
                  rolled back.)

```

Examples:

the only way to call this command

```
fw enable
```

### 5.3.3 disable

Makes firewall inactive (it will not touch any packets) immediately and after reboot

Synopsis:

```
fw disable [-h] [--unconditionally]
```

Detailed description of named arguments:

```

-h, --help      show this help message and exit
--unconditionally  Prevent connectivity checking after executing this
                  command (without this option user may be asked to confirm
                  that after command execution he has not lost connection
                  to the device, without such confirmation command would be
                  rolled back.)

```

Examples:

the only way to call this command

```
fw disable
```

### 5.3.4 set\_config

Restores presets from json file. Note that factory presets cannot be modified with this command.

Synopsis:

```
fw set_config [-h] --filename FILENAME [--unconditionally]
```

Detailed description of named arguments:

```

-h, --help      show this help message and exit
--filename FILENAME  json filename
--unconditionally  Prevent connectivity checking after executing this
                  command (without this option user may be asked to
                  confirm that after command execution he has not lost
                  connection to the device, without such confirmation
                  command would be rolled back.)

```

Examples:

```
fw set_config --filename firewall_config.json
```

## 5.3.5 get\_config

Stores firewall config (including all presets) in file `firewall_config.json`

Synopsis:

```
fw get_config [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

Examples:

the only way to call this command

```
fw get_config
```

## 5.3.6 show

Shows firewall configuration in terse way (i.e. notes will be hidden, use `{SUBPARSER_PRESET}` print with name of selected preset to see also notes

Synopsis:

```
fw show [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

Examples:

the only way to call this command

```
fw show
```

## 5.3.7 commit

If transaction has been started and not rolled backed yet (currently transaction timeout is always 30 seconds, but it will be configurable in the future) this command can be executed to prevent rollback and finish transaction immediately.

Synopsis:

```
fw commit [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

Examples:

the only way to call this command

```
fw commit
```

## 5.3.8 cleanup

If transaction was not finished by commit nor rollback and firewall configuration management daemon was restarted (e.g. due to power failure or crash) unclean state on disk may prevent any other transactions to be performed indefinitely. This command allows to recover from such state. Cleanup will first try to commit transaction, and if it fails it will remove leftovers. Restoring config from backup after using cleanup is recommended.

Synopsis:

```
fw cleanup [-h]
```

Detailed description of named arguments:

```
-h, --help show this help message and exit
```

Examples:

the only way to call this command

```
fw cleanup
```

## 5.3.9 reload

Reloads firewall configuration. If firewall has some state (e.g. is tracking existing connections) it will be reset.

Synopsis:

```
fw reload [-h]
```

Detailed description of named arguments:

```
-h, --help show this help message and exit
```

Examples:

the only way to call this command

```
fw reload
```

## 5.3.10 preset

Manages firewall prests — creation, marking as being edited, saving, and most importantly selecting the preset being used by EG for actual firewall configuration.

This command has following subcommands:

create	create new preset <b>in</b> being_edited state
delete	delete preset currently being_edited
edit	mark saved preset <b>as</b> being_edited (allows to change its contents, but prevents selecting it <b>as</b> current one)
save	mark preset being_edited <b>as</b> saved
select	select saved preset <b>for</b> use
list	list existing presets (both saved <b>and</b> being_edited)
print	print contents of preset(s) (whole <b>or</b> just a part)

Detailed description of named arguments:

```
-h, --help show this help message and exit
```

## Examples:

selects allow\_all preset for firewall configuration, if firewall was already enabled, new preset will be immediately applied

```
fw preset select allow_all
```

creates new being edited preset my\_own as copy of allow\_management preset

```
fw preset create my_own -s allow_management
```

## create

This command creates a new preset in being\_edited state. If --source option is given the new one will be a copy of the pointed source preset. This is atomic operation – even if more than one actor can access EG at the same time they will receive error if they try to perform conflicting atomic actions. Atomic operations are: preset selection, creating new preset, saving or making preset edited, reading all presets for backup or restoring all presets from backup.

Synopsis:

```
fw preset create [-h] [-s SOURCE] name
```

Detailed description of positional arguments:

name	Name of the preset to create. No patterns allowed.
------	--

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
-s SOURCE, --source SOURCE	Name of preset which shall be source of data <b>for</b> preset being_edited. Shell glob patterns may be used, but exactly one name must match pattern.

Examples:

create a new preset named better\_foo as a copy of good\_old\_foo

```
fw preset create better_foo --source good_old_foo
```

## delete

This command removes existing preset. Before removal preset must be in being\_edited state (see option --make\_edited). Removed preset cannot be restored – use backup instead.

Synopsis:

```
fw preset delete [-h] [-E] [name]
```

Detailed description of positional arguments:

name	Name of the preset being_edited which will be affected. Shell glob patterns may be used but shall match exactly one preset. If skipped this param defaults to '*' <b>and</b> because normally only one preset <b>is</b> being edited, so this argument <b>is</b> usually skipped.
------	---

Detailed description of named arguments:

```

-h, --help      show this help message and exit
-E, --make_edited  Mark saved preset as being edited one before performing
                   other actions, giving this option is the same as if
                   separate command `edit` was executed by the user just
                   before this command --- it may fail if preset is already
                   being edited, or if another user tried to make preset
                   edited at the same time
  
```

Examples:

first make preset good\_old\_foo editable (this step may fail, which will prevent removal), then remove it

```
fw preset delete good_old_foo --make_edited
```

remove better\_foo – this will fail if it is not being\_edited

```
fw preset delete better_foo
```

remove preset which name ends with foo – this will fail if there is no such preset being edited already

```
fw preset delete '*foo'
```

## edit

This command can be applied on saved preset to make it editable. Editable presets cannot be accidentally selected, and saved presets cannot be accidentally edited or removed. Because of this allowing to edit selected preset makes no sense – the whole idea is to prevent potentially incomplete preset from being selected. To modify selected preset you need to make a copy of it (see command `create -s`), then make changes, then save and select the copy. This is atomic operation – even if more than one actor can access EG at the same time they will receive error if they try to perform conflicting atomic actions. Atomic operations are: preset selection, creating new preset, saving or making preset edited, reading all presets for backup or restoring all presets from backup. Note that after starting the edition of the preset following editions are not atomic and if more than one actor performs them at the same time result might be unexpected – it is user responsibility to ensure that second actor will not start modifying preset already in being\_edited state before first actor finished his editions!

Synopsis:

```
fw preset edit [-h] [name]
```

Detailed description of positional arguments:

name	Name of saved preset. Shell glob patterns may be used but pattern must match exactly one preset name. If omitted defaults to '*'.
------	---

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

Examples:

make preset good\_old\_foo editable

```
fw preset edit good_old_foo
```

## save

This command can be applied on being\_edited preset to make it saved. Optionally a new name can be given to the preset during this operation. Editable presets cannot be accidentally selected, and saved presets cannot be accidentally edited or removed. This is atomic operation – even if more than one actor can access EG at the same time they will receive error if they try to perform conflicting atomic actions. Atomic operations are: preset selection, creating new preset, saving or making preset edited, reading all presets for backup or restoring all presets from backup.

Synopsis:

```
fw preset save [-h] [-d DESTINATION] [name]
```

Detailed description of positional arguments:

name	Name of the preset being_edited which will be affected. Shell glob patterns may be used but shall <b>match</b> exactly one preset. If skipped this param defaults to '*' <b>and</b> because normally only one preset <b>is</b> being edited, so this argument <b>is</b> usually skipped.
------	--

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
-d DESTINATION, --destination DESTINATION	Optional name under which currently being_edited preset shall be saved, <b>if not</b> given current name of preset being_edited will be used

Examples:

assuming only one preset is being edited currently save it under name new\_name

```
fw preset save -d new_name
```

save preset which name starts with my\_ (there must be exactly one such preset in being edited state, but there may be other being edited presets whose names start differently)

```
fw preset save 'my_*'
```

save the only being edited preset

```
fw preset save
```

## select

This command can be applied on saved preset to apply its contents as current configuration of EG. Any previously selected preset will cease to be selected anymore. This operation may require confirmation by the user after it is applied to prevent accidental loss of communication between user and EG. If such confirmation is not received it will be rolled back. If such confirmation is required, then operation starts at the moment of execution and ends at the moment it is rolled back or committed. Selected preset cannot be made editable. This is atomic operation – even if more than one actor can access EG at the same time they will receive error if they try to perform conflicting atomic actions. Atomic operations are: preset selection, creating new preset, saving or making preset edited, reading all presets for backup or restoring all presets from backup.

Synopsis:

```
fw preset select [-h] [--unconditionally] [name]
```

Detailed description of positional arguments:

name	Optional shell glob pattern to limit names of presets to <code>print</code> (defaults to <code>'*'</code> )
------	--

Detailed description of named arguments:

<code>-h, --help</code>	show this help message <b>and</b> exit
<code>--unconditionally</code>	Prevent connectivity checking after executing this command (without this option user may be asked to confirm that after command execution he has <b>not</b> lost connection to the device, without such confirmation command would be rolled back.)

Examples:

select and apply configuration in preset `location2_config`

```
fw preset select location2_config
```

## list

Lists existing presets (optionally limiting the result to presets matching glob pattern. Useful before executing commands to which concrete name is needed, or to check if preset is saved or being edited.

Synopsis:

```
fw preset list [-h] [name]
```

Detailed description of positional arguments:

name	Optional shell glob pattern to limit names returned (defaults to <code>'*'</code> )
------	---

Detailed description of named arguments:

<code>-h, --help</code>	show this help message <b>and</b> exit
-------------------------	--

Examples:

list all presets

```
fw preset list
```

list presets which names start with an 'a' and end with an 'x'

```
fw preset list 'a*x'
```

## print

Prints contents of preset(s). For presets with multipart structure, if only one part is interesting output may be limited by giving the `-part` argument.

Synopsis:

```
fw preset print [-h] [-p PART] [name]
```

Detailed description of positional arguments:

name	Optional shell glob pattern to limit names of presets to <code>print</code> (defaults to <code>'*'</code> )
------	---

Detailed description of named arguments:

<code>-h, --help</code>	show this help message <b>and</b> exit
<code>-p PART, --part PART</code>	Part (at least container of rules) of preset which shall be printed. Whole preset will printed <b>if not</b> given.

Examples:

print contents of part foo/bar/baz in all presets

<code>fw preset print --part foo/bar/baz</code>
---

print contents of whole foobar preset

<code>fw preset print foobar</code>
-------------------------------------

### 5.3.11 modify

Modifies contents of preset. Before actual modification can happen preset has to be in `being_edited` state (see `-E` in subcommands of this command and commands `fw preset edit` and `fw preset create`).

This command has following subcommands:

<code>copy</code>	copy a part of another preset to preset <code>being_edited</code>
<code>erase</code>	erase a part of preset <code>being_edited</code>
<code>set_policy</code>	<code>set</code> a default treatment of packets <b>if</b> no other rule matches
<code>common</code>	modify common filtering rules (part <code>inet/filter/common/mgmtd</code> )
<code>input</code>	modify filtering rules on packets targeted to EG (part <code>inet/filter/input/mgmtd</code> )
<code>output</code>	modify filtering rules on packets created by EG (part <code>inet/filter/output/mgmtd</code> )
<code>forward</code>	modify filtering rules on packets routed through EG (part <code>inet/filter/forward/mgmtd</code> )
<code>ingress</code>	Modify rules on packets routed through EG (part <code>netdev/ingress</code> )
<code>create-chain-ingress</code>	Create a chain <b>with</b> ingress hook (part <code>netdev/ingress</code> ).
<code>remove-chain-ingress</code>	Remove a chain <b>with</b> ingress hook (part <code>netdev/ingress</code> ).
<code>nat_pre</code>	modify nat rules applied before routing <b>and</b> filtering (part <code>ip/nat/prerouting/mgmtd</code> )
<code>nat_post</code>	modify nat rules applied after routing <b>and</b> filtering (part <code>ip/nat/postrouting/mgmtd</code> )
<code>nat_n_on_n</code>	allow creation of n:n static NAT <b>with</b> public <b>and</b> private IP addresses
<code>masquerade</code>	allow hiding private subnet <b>or</b> interface behind public IP of another interface
<code>snat</code>	allow hiding private subnet <b>or</b> interface behind public IP of another interface
<code>port_forward</code>	allow keeping a service running on a private IP available through public IP

Detailed description of named arguments:

<code>-h, --help</code>	show this help message <b>and</b> exit
-------------------------	--

Examples:

copy part `inet/filter/common` from preset `foo` to currently being edited preset (we did not provide `--name` option, hence only one preset is currently being edited)

```
fw modify copy -s foo -p inet/filter/common
```

first tries to mark saved preset `bar` as being edited, if it succeeds adds new masquerade rule named `masq_lan1` which will cause interface `lan1` to be treated as public one

```
fw modify masquerade --name bar -E add masq_lan1 --public_interface lan1
```

allows any incoming packets to port 22

```
fw modify input add allow_incoming_ssh -p ssh -v accept
```

disallows any outgoing packets not allowed by a specific rule — in connection with previous example ssh will not work, because outgoing traffic will be blocked

```
fw modify set_policy -p inet/filter/output drop
```

allows any outgoing packets belonging to (or related to) existing connections — this rectifies issue created by the drop policy from previous example because incoming packets will be allowed to port 22 (so connection will be created) and any packets related to existing connection will be allowed on output

```
fw modify output add allow_related --related -v accept
```

## copy

Copies a part of another preset to preset being\_edited. Useful when building new preset from parts of other existing presets by copying and erasing.

Synopsis:

```
fw modify copy [-h] [-n NAME] -s SOURCE [-p PART] [-E]
```

Detailed description of named arguments:

<code>-h, --help</code>	show this help message and exit
<code>-n NAME, --name NAME</code>	Name of the preset being_edited which will be affected. Shell glob patterns may be used but shall match exactly one preset. If skipped this param defaults to '*' and because normally only one preset is being edited, so this argument is usually skipped.
<code>-s SOURCE, --source SOURCE</code>	Name of preset which shall be source of data for preset being_edited. Shell glob patterns may be used, but exactly one name must match pattern.
<code>-p PART, --part PART</code>	Part (at least container of rules) of preset which shall be copied. Whole source preset will be copied if not given.
<code>-E, --make_edited</code>	Mark saved preset as being edited one before performing other actions, giving this option is the same as if separate command <code>'preset edit'</code> was executed by the user just before this command --- it may fail if preset is already being edited, or if another user tried to make preset edited at the same time

Examples:

copy part `inet/filter/common` from preset `foo` to currently being edited preset (we did not provide `--name` option, hence only one preset is currently being edited)

```
fw modify copy -s foo -p inet/filter/common
```

## erase

Erases a part of preset being\_edited. If the part is container for other parts erasing is equivalent to recreating erased part as copy from alllow\_all preset. Useful when building new preset from parts of other existing presets by copying and erasing.

Synopsis:

```
fw modify erase [-h] [-n NAME] [-p PART] [-E]
```

Detailed description of named arguments:

<b>-h, --help</b>	show this help message and exit
<b>-n NAME, --name NAME</b>	Name of the preset being_edited which will be affected. Shell glob patterns may be used but shall match exactly one preset. If skipped this param defaults to '*' and because normally only one preset is being edited, so this argument is usually skipped.
<b>-p PART, --part PART</b>	Part of preset which shall be erased. Whole preset will be affected if this parameter is not given.
<b>-E, --make_edited</b>	Mark saved preset as being edited one before performing other actions, giving this option is the same as if separate command `preset edit` was executed by the user just before this command --- it may fail if preset is already being edited, or if another user tried to make preset edited at the same time

Examples:

marks save presed foo as being edited and removes part inet/filter/common from it

```
fw modify erase -E -n foo -p inet/filter/common
```

## set\_policy

Synopsis:

```
fw modify set_policy [-h] [-n NAME] [-p PART] [-r] [-E] {accept,drop}
```

Detailed description of positional arguments:

<b>{accept,drop}</b>	drop <b>is</b> definitive, accept means that later chains will see the packet <b>and</b> may drop it later
----------------------	--

Detailed description of named arguments:

<b>-h, --help</b>	show this help message and exit
<b>-n NAME, --name NAME</b>	Name of the preset being_edited which will be affected. Shell glob patterns may be used but shall match exactly one preset. If skipped this param defaults to '*' and because normally only one preset is being edited, so this argument is usually skipped.
<b>-p PART, --part PART</b>	Part of preset which will be affected
<b>-r, --recursive</b>	If given policy will be set recursively in all subparts of part where applicable. If not given policy will be set only on the part selected (and the part must be having a policy)

(continues on next page)

(continued from previous page)

<b>-E, --make_edited</b>	Mark saved preset as being edited one before performing other actions, giving this option is the same as if separate command `preset edit` was executed by the user just before this command --- it may fail if preset is already being edited, or if another user tried to make preset edited at the same time
--------------------------	---

Sets policy which affects packets not matched by other specific rules. Option -r allows to set policy recursively in all subparts of part given by -p. Affected subparts list is returned by this command. Not matching any subpart is reported as error.

### Examples

The following two commands will lead to dropping by default any externally generated packets, and accepting by default any packets originated from the Edge Gateway.

<code>fw modify set_policy -r -p inet/filter drop</code>
<code>fw modify set_policy -p inet/filter/output accept</code>

### System behavior

Note that drops from rules are immediate, and drop from policy happens only after all rules in a part have been checked. Note that accept from rule or policy in one part is not final, because packet may be reevaluated but another part later. In general NAT prerouting rules are executed first, then filter rules are executed, finally NAT postrouting rules happen. If there is some more complicated preset, its ordering of rules shall be described in notes which accompany it.

## common

Modifies single filtering rule common for packets incoming, outgoing and forwarded by EG (part `inet/filter/common/mgmtd`). The `mgmtd` indicates that rules are directly editable by the user. There might be other parts in factory prepared presets which can be copied with help of `copy` command, but which cannot be modified to avoid hard to detect inconsistencies in firewall rules.

### Synopsis:

<code>fw modify common [-h] [-n NAME] [-v {accept,drop}]</code>
<code>[-l {ip,ip6,tcp,udp,sctp,icmp,icmpv6}]</code>
<code>[-p DESTINATION_PORT] [-P SOURCE_PORT] [-s SOURCE_IP]</code>
<code>[-S SOURCE_IP6] [-t DESTINATION_IP]</code>
<code>[-T DESTINATION_IP6] [-r] [-i INPUT_INTERFACE]</code>
<code>[-o OUTPUT_INTERFACE] [-M RAW_MATCH] [-A RAW_ACTION]</code>
<code>[-d NOTES] [-E]</code>
<code>{add,remove,edit,comment,uncomment} rule_name</code>

### Detailed description of positional arguments:

<code>{add,remove,edit,comment,uncomment}</code>	What to do <code>with</code> a rule
<code>rule_name</code>	Name of the rule to be affected

### Detailed description of named arguments:

```

-h, --help      show this help message and exit
-n NAME, --name NAME  Name of the preset being_edited which will be
                      affected. Shell glob patterns may be used but shall
                      match exactly one preset. If skipped this param
                      defaults to '*' and because normally only one preset
                      is being edited, so this argument is usually skipped.
-v {accept,drop}, --verdict {accept,drop}
                      drop or accept packet, if not given will be inverse of
                      policy at the time of rule addition, obviously if
                      there is no policy it cannot be skipped
-l {ip,ip6,tcp,udp,sctp,icmp,icmpv6}, --protocol {ip,ip6,tcp,udp,sctp,icmp,icmpv6}
                      match only packets of given protocol
-p DESTINATION_PORT, --destination_port DESTINATION_PORT
                      match TCP and UDP packets with given destination port
                      (use --protocol if you want to match only TCP or only
                      UDP)
-P SOURCE_PORT, --source_port SOURCE_PORT
                      match TCP and UDP packets with given source port (use
                      --protocol if you want to match only TCP or only UDP)
-s SOURCE_IP, --source_ip SOURCE_IP
                      match only IPv4 packets with given source address
                      (accepts also: IP_ADDRESS/subnet)
-S SOURCE_IP6, --source_ip6 SOURCE_IP6
                      match only IPv6 packets with given source address
                      (accepts also: IP_ADDRESS/subnet)
-t DESTINATION_IP, --destination_ip DESTINATION_IP
                      match only IPv4 packets with given destination address
                      (accepts also: IP_ADDRESS/subnet)
-T DESTINATION_IP6, --destination_ip6 DESTINATION_IP6
                      match only IPv6 packets with given destination address
                      (accepts also: IP_ADDRESS/subnet)
-r, --related
                      match packets of (or related to) previously accepted
                      connection --- note that to use --related you need
                      another rule which will accept the initial packet of a
                      connection, (for example you have a rule which accepts
                      all outgoing packets and a rule which accepts related
                      incoming packets)
-i INPUT_INTERFACE, --input_interface INPUT_INTERFACE
                      match packets which entered via given interface
-o OUTPUT_INTERFACE, --output_interface OUTPUT_INTERFACE
                      match packets which would exit via given interface
-M RAW_MATCH, --raw_match RAW_MATCH
                      value will be used in raw form for matching; Warning
                      --- in case of invalid contents error message will not
                      point to exact place of error
-A RAW_ACTION, --raw_action RAW_ACTION
                      value will be used in raw form as action to be
                      executed on matched packets; Warning --- in case of
                      invalid contents error message will not point to exact
                      place of error
-d NOTES, --description NOTES, --notes NOTES
                      additional notes about rule
-E, --make_edited
                      Mark saved preset as being edited one before
                      performing other actions, giving this option is the
                      same as if separate command `preset edit` was executed
                      by the user just before this command --- it may fail
                      if preset is already being edited, or if another user
                      tried to make preset edited at the same time

```

Examples:

add a new rule (with action not matching description!)

```
fw modify common add drop_smtp -l tcp -p 25 -v accept -d "This rule shall drop any SMTP packets"
```

correct previously created rule

```
fw modify common edit drop_smtp -l tcp -p 25 -v drop
```

## input

Modifies single rule in part `inet/filter/input/mgmtd`. The `mgmtd` indicates that rules are directly editable by the user. There might be other parts in factory prepared presets which can be copied with help of `copy` command, but which cannot be modified to avoid hard to detect inconsistencies in firewall rules.

Synopsis:

```
fw modify input [-h] [-n NAME] [-v {accept,drop}]
  [-l {ip,ip6,tcp,udp,sctp,icmp,icmpv6}]
  [-p DESTINATION_PORT] [-P SOURCE_PORT] [-s SOURCE_IP]
  [-S SOURCE_IP6] [-t DESTINATION_IP]
  [-T DESTINATION_IP6] [-r] [-i INPUT_INTERFACE]
  [-o OUTPUT_INTERFACE] [-M RAW_MATCH] [-A RAW_ACTION]
  [-d NOTES] [-E]
  {add,remove,edit,comment,uncomment} rule_name
```

Detailed description of positional arguments:

{add,remove,edit,comment,uncomment}	What to do <code>with</code> a rule
rule_name	Name of the rule to be affected

Detailed description of named arguments:

-h, --help	show this help message and exit
-n NAME, --name NAME	Name of the preset being_edited which will be affected. Shell glob patterns may be used but shall match exactly one preset. If skipped this param defaults to '*' and because normally only one preset is being edited, so this argument is usually skipped.
-v {accept,drop}, --verdict {accept,drop}	drop or accept packet, if not given will be inverse of policy at the time of rule addition, obviously if there is no policy it cannot be skipped
-l {ip,ip6,tcp,udp,sctp,icmp,icmpv6}, --protocol {ip,ip6,tcp,udp,sctp,icmp,icmpv6}	match only packets of given protocol
-p DESTINATION_PORT, --destination_port DESTINATION_PORT	match TCP and UDP packets with given destination port (use --protocol if you want to match only TCP or only UDP)
-P SOURCE_PORT, --source_port SOURCE_PORT	match TCP and UDP packets with given source port (use --protocol if you want to match only TCP or only UDP)
-s SOURCE_IP, --source_ip SOURCE_IP	match only IPv4 packets with given source address (accepts also: IP_ADDRESS/subnet)
-S SOURCE_IP6, --source_ip6 SOURCE_IP6	match only IPv6 packets with given source address (accepts also: IP_ADDRESS/subnet)
-t DESTINATION_IP, --destination_ip DESTINATION_IP	match only IPv4 packets with given destination address

(continues on next page)

(continued from previous page)

```

  (accepts also: IP_ADDRESS/subnet)
-T DESTINATION_IP6, --destination_ip6 DESTINATION_IP6
  match only IPv6 packets with given destination address
  (accepts also: IP_ADDRESS/subnet)
-r, --related
  match packets of (or related to) previously accepted
  connection --- note that to use --related you need
  another rule which will accept the initial packet of a
  connection, (for example you have a rule which accepts
  all outgoing packets and a rule which accepts related
  incoming packets)
-i INPUT_INTERFACE, --input_interface INPUT_INTERFACE
  match packets which entered via given interface
-o OUTPUT_INTERFACE, --output_interface OUTPUT_INTERFACE
  match packets which would exit via given interface
-M RAW_MATCH, --raw_match RAW_MATCH
  value will be used in raw form for matching; Warning
  --- in case of invalid contents error message will not
  point to exact place of error
-A RAW_ACTION, --raw_action RAW_ACTION
  value will be used in raw form as action to be
  executed on matched packets; Warning --- in case of
  invalid contents error message will not point to exact
  place of error
-d NOTES, --description NOTES, --notes NOTES
  additional notes about rule
-E, --make_edited
  Mark saved preset as being edited one before
  performing other actions, giving this option is the
  same as if separate command `preset edit` was executed
  by the user just before this command --- it may fail
  if preset is already being edited, or if another user
  tried to make preset edited at the same time

```

Examples:

add a new rule (with action not matching description!)

```
fw modify input add drop_smtp -l tcp -p 25 -v accept -d "This rule shall drop any SMTP packets"
```

correct previously created rule

```
fw modify input edit drop_smtp -l tcp -p 25 -v drop
```

## output

Modifies single rule on packets created by EG (part inet/filter/output/mgmt). The mgmt indicates that rules are directly editable by the user. There might be other parts in factory prepared presets which can be copied with help of copy command, but which cannot be modified to avoid hard to detect inconsistencies in firewall rules.

Synopsis:

```

fw modify output [-h] [-n NAME] [-v {accept,drop}]
  [-l {ip,ip6,tcp,udp,sctp,icmp,icmpv6}]
  [-p DESTINATION_PORT] [-P SOURCE_PORT] [-s SOURCE_IP]
  [-S SOURCE_IP6] [-t DESTINATION_IP]
  [-T DESTINATION_IP6] [-r] [-i INPUT_INTERFACE]
  [-o OUTPUT_INTERFACE] [-M RAW_MATCH] [-A RAW_ACTION]
  [-d NOTES] [-E]
  {add,remove,edit,comment,uncomment} rule_name

```

Detailed description of positional arguments:

{add,remove,edit,comment,uncomment}	What to do <b>with</b> a rule
rule_name	Name of the rule to be affected

Detailed description of named arguments:

```

-h, --help          show this help message and exit
-n NAME, --name NAME  Name of the preset being_edited which will be
                      affected. Shell glob patterns may be used but shall
                      match exactly one preset. If skipped this param
                      defaults to '*' and because normally only one preset
                      is being edited, so this argument is usually skipped.
-v {accept,drop}, --verdict {accept,drop}
                      drop or accept packet, if not given will be inverse of
                      policy at the time of rule addition, obviously if
                      there is no policy it cannot be skipped
-l {ip,ip6,tcp,udp,sctp,icmp,icmpv6}, --protocol {ip,ip6,tcp,udp,sctp,icmp,icmpv6}
                      match only packets of given protocol
-p DESTINATION_PORT, --destination_port DESTINATION_PORT
                      match TCP and UDP packets with given destination port
                      (use --protocol if you want to match only TCP or only
                      UDP)
-P SOURCE_PORT, --source_port SOURCE_PORT
                      match TCP and UDP packets with given source port (use
                      --protocol if you want to match only TCP or only UDP)
-s SOURCE_IP, --source_ip SOURCE_IP
                      match only IPv4 packets with given source address
                      (accepts also: IP_ADDRESS/subnet)
-S SOURCE_IP6, --source_ip6 SOURCE_IP6
                      match only IPv6 packets with given source address
                      (accepts also: IP_ADDRESS/subnet)
-t DESTINATION_IP, --destination_ip DESTINATION_IP
                      match only IPv4 packets with given destination address
                      (accepts also: IP_ADDRESS/subnet)
-T DESTINATION_IP6, --destination_ip6 DESTINATION_IP6
                      match only IPv6 packets with given destination address
                      (accepts also: IP_ADDRESS/subnet)
-r, --related
                      match packets of (or related to) previously accepted
                      connection --- note that to use --related you need
                      another rule which will accept the initial packet of a
                      connection, (for example you have a rule which accepts
                      all outgoing packets and a rule which accepts related
                      incoming packets)
-i INPUT_INTERFACE, --input_interface INPUT_INTERFACE
                      match packets which entered via given interface
-o OUTPUT_INTERFACE, --output_interface OUTPUT_INTERFACE
                      match packets which would exit via given interface
-M RAW_MATCH, --raw_match RAW_MATCH
                      value will be used in raw form for matching; Warning
                      --- in case of invalid contents error message will not
                      point to exact place of error
-A RAW_ACTION, --raw_action RAW_ACTION
                      value will be used in raw form as action to be
                      executed on matched packets; Warning --- in case of
                      invalid contents error message will not point to exact
                      place of error
-d NOTES, --description NOTES, --notes NOTES
                      additional notes about rule
-E, --make_edited
                      Mark saved preset as being edited one before
                      performing other actions, giving this option is the

```

(continues on next page)

(continued from previous page)

same as if separate command `preset edit` was executed by the user just before this command --- it may fail if preset is already being edited, or if another user tried to make preset edited at the same time

Examples:

add a new rule (with action not matching description!)

```
fw modify output add drop_smtp -l tcp -p 25 -v accept -d "This rule shall drop any SMTP packets"
```

correct previously created rule

```
fw modify output edit drop_smtp -l tcp -p 25 -v drop
```

## forward

Modifies single rule on packets routed through EG (part inet/filter/forward/mgmt). The mgmtd indicates that rules are directly editable by the user. There might be other parts in factory prepared presets which can be copied with help of copy command, but which cannot be modified to avoid hard to detect inconsistencies in firewall rules.

Synopsis:

```
fw modify forward [-h] [-n NAME] [-v {accept,drop}]
  [-l {ip,ip6,tcp,udp,sctp,icmp,icmpv6}]
  [-p DESTINATION_PORT] [-P SOURCE_PORT] [-s SOURCE_IP]
  [-S SOURCE_IP6] [-t DESTINATION_IP]
  [-T DESTINATION_IP6] [-r] [-i INPUT_INTERFACE]
  [-o OUTPUT_INTERFACE] [-M RAW_MATCH] [-A RAW_ACTION]
  [-d NOTES] [-E]
  {add,remove,edit,comment,uncomment} rule_name
```

Detailed description of positional arguments:

{add,remove,edit,comment,uncomment}	What to do <b>with</b> a rule
rule_name	Name of the rule to be affected

Detailed description of named arguments:

-h, --help	show this help message and exit
-n NAME, --name NAME	Name of the preset being_edited which will be affected. Shell glob patterns may be used but shall match exactly one preset. If skipped this param defaults to '*' and because normally only one preset is being edited, so this argument is usually skipped.
-v {accept,drop}, --verdict {accept,drop}	drop or accept packet, if not given will be inverse of policy at the time of rule addition, obviously if there is no policy it cannot be skipped
-l {ip,ip6,tcp,udp,sctp,icmp,icmpv6}, --protocol {ip,ip6,tcp,udp,sctp,icmp,icmpv6}	match only packets of given protocol
-p DESTINATION_PORT, --destination_port DESTINATION_PORT	match TCP and UDP packets with given destination port (use --protocol if you want to match only TCP or only UDP)
-P SOURCE_PORT, --source_port SOURCE_PORT	match TCP and UDP packets with given source port (use --protocol if you want to match only TCP or only UDP)

(continues on next page)

(continued from previous page)

```

-s SOURCE_IP, --source_ip SOURCE_IP
  match only IPv4 packets with given source address
  (accepts also: IP_ADDRESS/subnet)
-S SOURCE_IP6, --source_ip6 SOURCE_IP6
  match only IPv6 packets with given source address
  (accepts also: IP_ADDRESS/subnet)
-t DESTINATION_IP, --destination_ip DESTINATION_IP
  match only IPv4 packets with given destination address
  (accepts also: IP_ADDRESS/subnet)
-T DESTINATION_IP6, --destination_ip6 DESTINATION_IP6
  match only IPv6 packets with given destination address
  (accepts also: IP_ADDRESS/subnet)
-r, --related
  match packets of (or related to) previously accepted
  connection --- note that to use --related you need
  another rule which will accept the initial packet of a
  connection, (for example you have a rule which accepts
  all outgoing packets and a rule which accepts related
  incoming packets)
-i INPUT_INTERFACE, --input_interface INPUT_INTERFACE
  match packets which entered via given interface
-o OUTPUT_INTERFACE, --output_interface OUTPUT_INTERFACE
  match packets which would exit via given interface
-M RAW_MATCH, --raw_match RAW_MATCH
  value will be used in raw form for matching; Warning
  --- in case of invalid contents error message will not
  point to exact place of error
-A RAW_ACTION, --raw_action RAW_ACTION
  value will be used in raw form as action to be
  executed on matched packets; Warning --- in case of
  invalid contents error message will not point to exact
  place of error
-d NOTES, --description NOTES, --notes NOTES
  additional notes about rule
-E, --make_edited
  Mark saved preset as being edited one before
  performing other actions, giving this option is the
  same as if separate command `preset edit` was executed
  by the user just before this command --- it may fail
  if preset is already being edited, or if another user
  tried to make preset edited at the same time

```

**Examples:**

add a new rule (with action not matching description!)

```
fw modify forward add drop_smtp -l tcp -p 25 -v accept -d "This rule shall drop any SMTP packets"
```

correct previously created rule

```
fw modify forward edit drop_smtp -l tcp -p 25 -v drop
```

## ingress

Modifies single rule on packets routed through EG (part netdev/ingress). The `mgmt` indicates that rules are directly editable by the user. There might be other parts in factory prepared presets which can be copied with help of `copy` command, but which cannot be modified to avoid hard to detect inconsistencies in firewall rules.

Synopsis:

```
fw modify ingress [-h] [-n NAME] [-v {accept,drop}]
  [-l {ip,ip6,tcp,udp,sctp,icmp,icmpv6}]
  [-p DESTINATION_PORT] [-P SOURCE_PORT] [-s SOURCE_IP]
  [-S SOURCE_IP6] [-t DESTINATION_IP]
  [-T DESTINATION_IP6] [-r] [-i INPUT_INTERFACE]
  [-o OUTPUT_INTERFACE] [-M RAW_MATCH] [-A RAW_ACTION]
  [-d NOTES] [-E]
  chain_name {add,remove,edit,comment,uncomment}
  rule_name
```

Detailed description of positional arguments:

chain_name	name of the chain to modify
{add,remove,edit,comment,uncomment}	What to do <b>with</b> a rule
rule_name	Name of the rule to be affected

Detailed description of named arguments:

```
-h, --help          show this help message and exit
-n NAME, --name NAME  Name of the preset being_edited which will be
                      affected. Shell glob patterns may be used but shall
                      match exactly one preset. If skipped this param
                      defaults to '*' and because normally only one preset
                      is being edited, so this argument is usually skipped.
-v {accept,drop}, --verdict {accept,drop}
                      drop or accept packet, if not given will be inverse of
                      policy at the time of rule addition, obviously if
                      there is no policy it cannot be skipped
-l {ip,ip6,tcp,udp,sctp,icmp,icmpv6}, --protocol {ip,ip6,tcp,udp,sctp,icmp,icmpv6}
                      match only packets of given protocol
-p DESTINATION_PORT, --destination_port DESTINATION_PORT
                      match TCP and UDP packets with given destination port
                      (use --protocol if you want to match only TCP or only
                      UDP)
-P SOURCE_PORT, --source_port SOURCE_PORT
                      match TCP and UDP packets with given source port (use
                      --protocol if you want to match only TCP or only UDP)
-s SOURCE_IP, --source_ip SOURCE_IP
                      match only IPv4 packets with given source address
                      (accepts also: IP_ADDRESS/subnet)
-S SOURCE_IP6, --source_ip6 SOURCE_IP6
                      match only IPv6 packets with given source address
                      (accepts also: IP_ADDRESS/subnet)
-t DESTINATION_IP, --destination_ip DESTINATION_IP
                      match only IPv4 packets with given destination address
                      (accepts also: IP_ADDRESS/subnet)
-T DESTINATION_IP6, --destination_ip6 DESTINATION_IP6
                      match only IPv6 packets with given destination address
                      (accepts also: IP_ADDRESS/subnet)
-r, --related
                      match packets of (or related to) previously accepted
                      connection --- note that to use --related you need
                      another rule which will accept the initial packet of a
```

(continues on next page)

(continued from previous page)

```

connection, (for example you have a rule which accepts
all outgoing packets and a rule which accepts related
incoming packets)
-i INPUT_INTERFACE, --input_interface INPUT_INTERFACE
  match packets which entered via given interface
-o OUTPUT_INTERFACE, --output_interface OUTPUT_INTERFACE
  match packets which would exit via given interface
-M RAW_MATCH, --raw_match RAW_MATCH
  value will be used in raw form for matching; Warning
  --- in case of invalid contents error message will not
  point to exact place of error
-A RAW_ACTION, --raw_action RAW_ACTION
  value will be used in raw form as action to be
  executed on matched packets; Warning --- in case of
  invalid contents error message will not point to exact
  place of error
-d NOTES, --description NOTES, --notes NOTES
  additional notes about rule
-E, --make_edited
  Mark saved preset as being edited one before
  performing other actions, giving this option is the
  same as if separate command `preset edit` was executed
  by the user just before this command --- it may fail
  if preset is already being edited, or if another user
  tried to make preset edited at the same time

```

Examples:

add a new rule (with action not matching description!)

```
fw modify ingress add drop_smtp -l tcp -p 25 -v accept -d "This rule shall drop any SMTP packets"
```

correct previously created rule

```
fw modify ingress edit drop_smtp -l tcp -p 25 -v drop
```

## create-chain-ingress

Create a new chain with ingress hook for specified devices.

Synopsis:

```
fw modify create-chain-ingress [-h] [--chain-name CHAIN_NAME]
                               [--device {} [{} ...]] [-n NAME] [-E]
```

Detailed description of named arguments:

```

-h, --help          show this help message and exit
--chain-name CHAIN_NAME
  Name of the chain (default is name of the
  device/devices joined by '_').
--device {} [{} ...] LAN devices.
-n NAME, --name NAME Name of the preset being_edited which will be
  affected. Shell glob patterns may be used but shall
  match exactly one preset. If skipped this param
  defaults to '*' and because normally only one preset
  is being edited, so this argument is usually skipped.
-E, --make_edited
  Mark saved preset as being edited one before
  performing other actions, giving this option is the
  same as if separate command `preset edit` was executed

```

(continues on next page)

(continued from previous page)

by the user just before this command --- it may fail if preset is already being edited, or if another user tried to make preset edited at the same time

## remove-chain-ingress

Synopsis:

```
fw modify remove-chain-ingress [-h] [-n NAME] [-E] chain_name
```

Detailed description of positional arguments:

chain_name	Name of the chain.
------------	--------------------

Detailed description of named arguments:

-h, --help	show this help message and exit
-n NAME, --name NAME	Name of the preset being_edited which will be affected. Shell glob patterns may be used but shall match exactly one preset. If skipped this param defaults to '*' and because normally only one preset is being edited, so this argument is usually skipped.
-E, --make_edited	Mark saved preset as being edited one before performing other actions, giving this option is the same as if separate command `preset edit` was executed by the user just before this command --- it may fail if preset is already being edited, or if another user tried to make preset edited at the same time

## nat\_pre

Modifies single prerouting nat rule (part ip/nat/prerouting/mgmt). Note that there are also specialized nat related commands (nat\_n\_on\_n, masquerade, snat, port\_forward). The mgmt indicates that rules are directly editable by the user. There might be other parts in factory prepared presets which can be copied with help of copy command, but which cannot be modified to avoid hard to detect inconsistencies in firewall rules.

Synopsis:

```
fw modify nat_pre [-h] [-n NAME] [-v {accept,drop}]
  [-l {ip,ip6,tcp,udp,sctp,icmp,icmpv6}]
  [-p DESTINATION_PORT] [-P SOURCE_PORT] [-s SOURCE_IP]
  [-S SOURCE_IP6] [-t DESTINATION_IP]
  [-T DESTINATION_IP6] [-r] [-i INPUT_INTERFACE]
  [-o OUTPUT_INTERFACE] [-M RAW_MATCH] [-A RAW_ACTION]
  [-d NOTES] [-E]
  {add,remove,edit,comment,uncomment} rule_name
```

Detailed description of positional arguments:

{add,remove,edit,comment,uncomment}	What to do <b>with</b> a rule
rule_name	Name of the rule to be affected

Detailed description of named arguments:

-h, --help	show this help message and exit
-n NAME, --name NAME	Name of the preset being_edited which will be affected. Shell glob patterns may be used but shall

(continues on next page)

(continued from previous page)

```

  match exactly one preset. If skipped this param
  defaults to '*' and because normally only one preset
  is being edited, so this argument is usually skipped.

-v {accept,drop}, --verdict {accept,drop}
  drop or accept packet, if not given will be inverse of
  policy at the time of rule addition, obviously if
  there is no policy it cannot be skipped

-l {ip,ip6,tcp,udp,sctp,icmp,icmpv6}, --protocol {ip,ip6,tcp,udp,sctp,icmp,icmpv6}
  match only packets of given protocol

-p DESTINATION_PORT, --destination_port DESTINATION_PORT
  match TCP and UDP packets with given destination port
  (use --protocol if you want to match only TCP or only
  UDP)

-P SOURCE_PORT, --source_port SOURCE_PORT
  match TCP and UDP packets with given source port (use
  --protocol if you want to match only TCP or only UDP)

-s SOURCE_IP, --source_ip SOURCE_IP
  match only IPv4 packets with given source address
  (accepts also: IP_ADDRESS/subnet)

-S SOURCE_IP6, --source_ip6 SOURCE_IP6
  match only IPv6 packets with given source address
  (accepts also: IP_ADDRESS/subnet)

-t DESTINATION_IP, --destination_ip DESTINATION_IP
  match only IPv4 packets with given destination address
  (accepts also: IP_ADDRESS/subnet)

-T DESTINATION_IP6, --destination_ip6 DESTINATION_IP6
  match only IPv6 packets with given destination address
  (accepts also: IP_ADDRESS/subnet)

-r, --related
  match packets of (or related to) previously accepted
  connection --- note that to use --related you need
  another rule which will accept the initial packet of a
  connection, (for example you have a rule which accepts
  all outgoing packets and a rule which accepts related
  incoming packets)

-i INPUT_INTERFACE, --input_interface INPUT_INTERFACE
  match packets which entered via given interface

-o OUTPUT_INTERFACE, --output_interface OUTPUT_INTERFACE
  match packets which would exit via given interface

-M RAW_MATCH, --raw_match RAW_MATCH
  value will be used in raw form for matching; Warning
  --- in case of invalid contents error message will not
  point to exact place of error

-A RAW_ACTION, --raw_action RAW_ACTION
  value will be used in raw form as action to be
  executed on matched packets; Warning --- in case of
  invalid contents error message will not point to exact
  place of error

-d NOTES, --description NOTES, --notes NOTES
  additional notes about rule

-E, --make_edited
  Mark saved preset as being edited one before
  performing other actions, giving this option is the
  same as if separate command `preset edit` was executed
  by the user just before this command --- it may fail
  if preset is already being edited, or if another user
  tried to make preset edited at the same time

```

**Examples:**

add a new rule (with action not matching description!)

```
fw modify nat_pre add drop_smtp -l tcp -p 25 -v accept -d "This rule shall drop any SMTP packets"
```

correct previously created rule

```
fw modify nat_pre edit drop_smtp -l tcp -p 25 -v drop
```

## nat\_post

Modifies single postrouting nat rule (part ip/nat/postrouting/mgmt). Note that there are also specialized nat related commands (nat\_n\_on\_n, masquerade, snat, port\_forward). The mgmt indicates that rules are directly editable by the user. There might be other parts in factory prepared presets which can be copied with help of copy command, but which cannot be modified to avoid hard to detect inconsistencies in firewall rules.

Synopsis:

```
fw modify nat_post [-h] [-n NAME] [-v {accept,drop}]
                   [-l {ip,ip6,tcp,udp,sctp,icmp,icmpv6}]
                   [-p DESTINATION_PORT] [-P SOURCE_PORT]
                   [-s SOURCE_IP] [-S SOURCE_IP6] [-t DESTINATION_IP]
                   [-T DESTINATION_IP6] [-r] [-i INPUT_INTERFACE]
                   [-o OUTPUT_INTERFACE] [-M RAW_MATCH] [-A RAW_ACTION]
                   [-d NOTES] [-E]
                   {add,remove,edit,comment,uncomment} rule_name
```

Detailed description of positional arguments:

{add,remove,edit,comment,uncomment}	What to do <b>with</b> a rule
rule_name	Name of the rule to be affected

Detailed description of named arguments:

-h, --help	show this help message and exit
-n NAME, --name NAME	Name of the preset being_edited which will be affected. Shell glob patterns may be used but shall match exactly one preset. If skipped this param defaults to '*' and because normally only one preset is being edited, so this argument is usually skipped.
-v {accept,drop}, --verdict {accept,drop}	drop or accept packet, if not given will be inverse of policy at the time of rule addition, obviously if there is no policy it cannot be skipped
-l {ip,ip6,tcp,udp,sctp,icmp,icmpv6}, --protocol {ip,ip6,tcp,udp,sctp,icmp,icmpv6}	match only packets of given protocol
-p DESTINATION_PORT, --destination_port DESTINATION_PORT	match TCP and UDP packets with given destination port (use --protocol if you want to match only TCP or only UDP)
-P SOURCE_PORT, --source_port SOURCE_PORT	match TCP and UDP packets with given source port (use --protocol if you want to match only TCP or only UDP)
-s SOURCE_IP, --source_ip SOURCE_IP	match only IPv4 packets with given source address (accepts also: IP_ADDRESS/subnet)
-S SOURCE_IP6, --source_ip6 SOURCE_IP6	match only IPv6 packets with given source address (accepts also: IP_ADDRESS/subnet)
-t DESTINATION_IP, --destination_ip DESTINATION_IP	match only IPv4 packets with given destination address

(continues on next page)

(continued from previous page)

```
(accepts also: IP_ADDRESS/subnet)
-T DESTINATION_IP6, --destination_ip6 DESTINATION_IP6
    match only IPv6 packets with given destination address
    (accepts also: IP_ADDRESS/subnet)
-r, --related
    match packets of (or related to) previously accepted
    connection --- note that to use --related you need
    another rule which will accept the initial packet of a
    connection, (for example you have a rule which accepts
    all outgoing packets and a rule which accepts related
    incoming packets)
-i INPUT_INTERFACE, --input_interface INPUT_INTERFACE
    match packets which entered via given interface
-o OUTPUT_INTERFACE, --output_interface OUTPUT_INTERFACE
    match packets which would exit via given interface
-M RAW_MATCH, --raw_match RAW_MATCH
    value will be used in raw form for matching; Warning
    --- in case of invalid contents error message will not
    point to exact place of error
-A RAW_ACTION, --raw_action RAW_ACTION
    value will be used in raw form as action to be
    executed on matched packets; Warning --- in case of
    invalid contents error message will not point to exact
    place of error
-d NOTES, --description NOTES, --notes NOTES
    additional notes about rule
-E, --make_edited
    Mark saved preset as being edited one before
    performing other actions, giving this option is the
    same as if separate command `preset edit` was executed
    by the user just before this command --- it may fail
    if preset is already being edited, or if another user
    tried to make preset edited at the same time
```

## Examples:

add a new rule (with action not matching description!)

```
fw modify nat_post add drop_smtp -l tcp -p 25 -v accept -d "This rule shall drop any SMTP packets  
"
```

correct previously created rule

```
fw modify nat_post edit drop_smtp -l tcp -p 25 -v drop
```

**nat\_n\_on\_n**

Allows creation of n:n static NAT with public and private IP addresses. Traffic to public addresses will be redirected to private addresses, and traffic from private addresses will appear as if it originated from public addresses

### Synopsis:

```
fw modify nat_n_on_n [-h] [-n NAME]
                      [--public_interface PUBLIC_INTERFACE]
                      [--ip_public IP_PUBLIC] [--ip_private IP_PRIVATE]
                      [--mask MASK] [-d NOTES] [-E]
                      {add,remove,edit,comment,uncomment} rule name
```

#### Detailed description of positional arguments:

{add,remove,edit,comment,uncomment}	What to do <b>with</b> a rule
rule_name	Name of the rule to be affected

Detailed description of named arguments:

-h, --help	show this help message and exit
-n NAME, --name NAME	Name of the preset being_edited which will be affected. Shell glob patterns may be used but shall match exactly one preset. If skipped this param defaults to '*' and because normally only one preset is being edited, so this argument is usually skipped.
--public_interface PUBLIC_INTERFACE	optional interface name on which ip_public will be visible
--ip_public IP_PUBLIC	IP address --- traffic to ip_public will be redirected to ip_private, and traffic from ip_private will appear as if it originated from ip_public
--ip_private IP_PRIVATE	IP address --- see ip_public option
--mask MASK	optional netmask --- if not given 1:1 NAT will be done, if given only netmask bits of ip_a and ip_b will be translated (i.e. N:N nat will be performed)
-d NOTES, --description NOTES, --notes NOTES	additional notes about rule
-E, --make_edited	Mark saved preset as being edited one before performing other actions, giving this option is the same as if separate command `preset edit` was executed by the user just before this command --- it may fail if preset is already being edited, or if another user tried to make preset edited at the same time

Examples:

```
fw modify nat_n_on_n add from_lan1to2 --public_interface lan1 --ip_public 192.168.2.202 --ip_private 192.168.1.102
```

## masquerade

Allows hiding private subnet or interface behind public IP of another interface. To allow all needed traffic back firewall needs to track connections and protocols used by hidden machines. Automatically uses public IP of interface (which may be dynamic) and all connections are forgotten when interface goes down (difference from SNAT)

Synopsis:

```
fw modify masquerade [-h] [-n NAME]
                      [--public_interface PUBLIC_INTERFACE]
                      [--private_interface PRIVATE_INTERFACE]
                      [--ip_private IP_PRIVATE]
                      [--mask_private MASK_PRIVATE] [-d NOTES] [-E]
                      {add,remove,edit,comment,uncomment} rule_name
```

Detailed description of positional arguments:

{add,remove,edit,comment,uncomment}	What to do <b>with</b> a rule
rule_name	Name of the rule to be affected

Detailed description of named arguments:

```

-h, --help      show this help message and exit
-n NAME, --name NAME  Name of the preset being_edited which will be
                      affected. Shell glob patterns may be used but shall
                      match exactly one preset. If skipped this param
                      defaults to '*' and because normally only one preset
                      is being edited, so this argument is usually skipped.
--public_interface PUBLIC_INTERFACE
                  interface with public IP
--private_interface PRIVATE_INTERFACE
                  optional, interface behind which private subnets exist
--ip_private IP_PRIVATE
                  optional, private IP address or subnet (if
                  mask_private is also given)
--mask_private MASK_PRIVATE
                  optional netmask (may be given only if ip_private is
                  also given)
-d NOTES, --description NOTES, --notes NOTES
                  additional notes about rule
-E, --make_edited
                  Mark saved preset as being edited one before
                  performing other actions, giving this option is the
                  same as if separate command `preset edit` was executed
                  by the user just before this command --- it may fail
                  if preset is already being edited, or if another user
                  tried to make preset edited at the same time

```

Examples:

simplest masquerade where lan2 has public dynamically assigned IP

```
fw modify masquerade add masq_lan2 --public_interface lan2
```

## snat

Allows hiding private subnet or interface behind public IP of another interface. To allow all needed traffic back firewall needs to track connections and protocols used by hidden machines. Public IP must be static, and connections may survive interface going down temporarily

Synopsis:

```

fw modify snat [-h] [-n NAME] [--ip_public IP_PUBLIC]
                [--public_interface PUBLIC_INTERFACE]
                [--private_interface PRIVATE_INTERFACE]
                [--ip_private IP_PRIVATE] [--mask_private MASK_PRIVATE]
                [-d NOTES] [-E]
                {add,remove,edit,comment,uncomment} rule_name

```

Detailed description of positional arguments:

{add,remove,edit,comment,uncomment}	What to do <b>with</b> a rule
rule_name	Name of the rule to be affected

Detailed description of named arguments:

```

-h, --help      show this help message and exit
-n NAME, --name NAME  Name of the preset being_edited which will be
                      affected. Shell glob patterns may be used but shall
                      match exactly one preset. If skipped this param
                      defaults to '*' and because normally only one preset
                      is being edited, so this argument is usually skipped.

```

(continues on next page)

(continued from previous page)

```

--ip_public IP_PUBLIC
  Public IP address used as disguise for outgoing
  traffic of private network
--public_interface PUBLIC_INTERFACE
  interface with public IP
--private_interface PRIVATE_INTERFACE
  optional, interface behind which private subnets exist
--ip_private IP_PRIVATE
  optional, private IP address or subnet (if
  mask_private is also given)
--mask_private MASK_PRIVATE
  optional netmask (may be given only if ip_private is
  also given)
-d NOTES, --description NOTES, --notes NOTES
  additional notes about rule
-E, --make_edited
  Mark saved preset as being edited one before
  performing other actions, giving this option is the
  same as if separate command `preset edit` was executed
  by the user just before this command --- it may fail
  if preset is already being edited, or if another user
  tried to make preset edited at the same time

```

Examples:

simplest SNAT with public ip 43.21.35.17 on lan2

```
fw modify snat add masq_lan2 --public_interface lan2 --public_ip 43.21.35.17
```

## port\_forward

Allows keeping a service running on a private IP available through public IP. 'Only TCP and UDP services are supported.

Synopsis:

```

fw modify port_forward [-h] [-n NAME]
  [--public_interface PUBLIC_INTERFACE]
  [--ip_public IP_PUBLIC]
  [--port_public PORT_PUBLIC]
  [--ip_private IP_PRIVATE]
  [--port_private PORT_PRIVATE]
  [--protocol PROTOCOL] [-d NOTES] [-E]
  {add,remove,edit,comment,uncomment} rule_name

```

Detailed description of positional arguments:

{add,remove,edit,comment,uncomment}	What to do <b>with</b> a rule
rule_name	Name of the rule to be affected

Detailed description of named arguments:

-h, --help	show this help message and exit
-n NAME, --name NAME	Name of the preset being_edited which will be       affected. Shell glob patterns may be used but shall       match exactly one preset. If skipped this param       defaults to '*' and because normally only one preset       is being edited, so this argument is usually skipped.
--public_interface PUBLIC_INTERFACE	

(continues on next page)

(continued from previous page)

```

optional, interface with public IP (to be used if
public IP is not known), if given only traffic
entering through this interface will be affected

--ip_public IP_PUBLIC
  optional, public IP address (shall always be used if
  known, if not given public_interface becomes
  mandatory)

--port_public PORT_PUBLIC
  mandatory, port to which traffic will be forwarded

--ip_private IP_PRIVATE
  mandatory, private IP address to which traffic will be
  forwarded

--port_private PORT_PRIVATE
  optional, allowed only if single protocol is being
  used in rule, modifies port in forwarded packets

--protocol PROTOCOL
  optional, "tcp", or "udp", or "both", if not given
  "tcp" will be assumed

-d NOTES, --description NOTES, --notes NOTES
  additional notes about rule

-E, --make_edited
  Mark saved preset as being edited one before
  performing other actions, giving this option is the
  same as if separate command `preset edit` was executed
  by the user just before this command --- it may fail
  if preset is already being edited, or if another user
  tried to make preset edited at the same time

```

Examples:

```
fw modify port_forward add foo --public_interface lan1 --port_public 4321 --ip_private 192.168.2.
  ↳20 --port_private 1234 --protocol udp
```

### 5.3.12 print

Similar to preset print but intended to print only single currently edited preset. If there is only one preset being edited name of the preset can be skipped. If there is more than one preset being edited, name of the preset must be given and it shall match only one of them. -part argument allows to limit output, e.g. in case of huge preset.

Synopsis:

```
fw print [-h] [-n NAME] [-p PART]
```

Detailed description of named arguments:

```

-h, --help
  show this help message and exit

-n NAME, --name NAME
  Name of the preset being_edited which will be
  affected. Shell glob patterns may be used but shall
  match exactly one preset. If skipped this param
  defaults to '*' and because normally only one preset
  is being edited, so this argument is usually skipped.

-p PART, --part PART
  Part (at least container of rules) of preset which
  shall be printed. Whole preset will printed if not
  given.

```

Examples:

print contents of the one and only currently being edited preset

```
fw print
```

## 5.4 Container management

```

FORMAT controls the output. Interpreted sequences are:
Usage: docker [OPTIONS] COMMAND
A self-sufficient runtime for containers
Common Commands:
  run      Create and run a new container from an image
  exec     Execute a command in a running container
  ps       List containers
  build    Build an image from a Dockerfile
  pull     Download an image from a registry
  push     Upload an image to a registry
  images   List images
  login    Authenticate to a registry
  logout   Log out from a registry
  search   Search Docker Hub for images
  version  Show the Docker version information
  info     Display system-wide information
Management Commands:
  builder  Manage builds
  buildx*  Docker Buildx
  checkpoint  Manage checkpoints
  compose*  Docker Compose
  container  Manage containers
  context    Manage contexts
  image     Manage images
  manifest  Manage Docker image manifests and manifest lists
  network   Manage networks
  plugin    Manage plugins
  system    Manage Docker
  trust     Manage trust on Docker images
  volume    Manage volumes
Swarm Commands:
  config  Manage Swarm configs
  node    Manage Swarm nodes
  secret  Manage Swarm secrets
  service Manage Swarm services
  stack   Manage Swarm stacks
  swarm   Manage Swarm
Commands:
  attach   Attach local standard input, output, and error streams to a running container
  commit   Create a new image from a container's changes
  cp       Copy files/folders between a container and the local filesystem
  create   Create a new container
  diff     Inspect changes to files or directories on a container's filesystem
  events   Get real time events from the server
  export   Export a container's filesystem as a tar archive
  history  Show the history of an image
  import   Import the contents from a tarball to create a filesystem image
  inspect  Return low-level information on Docker objects
  kill     Kill one or more running containers
  load    Load an image from a tar archive or STDIN
  logs    Fetch the logs of a container
  pause   Pause all processes within one or more containers
  port    List port mappings or a specific mapping for the container
  rename  Rename a container
  restart Restart one or more containers
  rm     Remove one or more containers
  rmi    Remove one or more images
  save   Save one or more images to a tar archive (streamed to STDOUT by default)

```

(continues on next page)

(continued from previous page)

```

start      Start one or more stopped containers
stats      Display a live stream of container(s) resource usage statistics
stop       Stop one or more running containers
tag        Create a tag TARGET_IMAGE that refers to SOURCE_IMAGE
top        Display the running processes of a container
unpause    Unpause all processes within one or more containers
update    Update configuration of one or more containers
wait      Block until one or more containers stop, then print their exit codes
Global Options:
  --config string      Location of client config files (default
                       "/root/.docker")
  -c, --context string  Name of the context to use to connect to the
                       daemon (overrides DOCKER_HOST env var and
                       default context set with "docker context use")
  -D, --debug          Enable debug mode
  -H, --host list      Daemon socket to connect to
  -l, --log-level string  Set the logging level ("debug", "info",
                         "warn", "error", "fatal") (default "info")
  --tls                Use TLS; implied by --tlsverify
  --tlscacert string   Trust certs signed only by this CA (default
                       "/root/.docker/ca.pem")
  --tlscert string     Path to TLS certificate file (default
                       "/root/.docker/cert.pem")
  --tlskey string      Path to TLS key file (default
                       "/root/.docker/key.pem")
  --tlsverify          Use TLS and verify the remote
  -v, --version         Print version information and quit

```

```

docker pull yoctobuild/yocto:first
docker images
docker ps
docker run -it -v yoctobuild/yocto:latest /bin/bash

```

## 5.5 Docker configuration

This command has following subcommands:

apply	Restart docker service to apply changes docker DNS configuration
compose	Manage docker compose files to be started automatically
dns	Add/remove docker DNS servers
params	Configure docker daemon <b>with</b> parameters {REQUIRES_APPLY}
auth	Authenticate to private repositories

get\_config option will generate docker-compose file for each currently running docker image that **was** created by the user. This application will ignore docker created via Azure Edge.

```
docker-config get_config
```

```
docker-config load_compose --filename [docker-compose yml file]
```

## 5.5.1 apply

Some of the CLI commands allow to change the docker config in small increments. Restarting whole docker service after each of such small increments would take long time and could unnecessarily disrupt continuity of work of the containers. Therefore documentation of such CLI commands notes, that you need to additionally trigger ‘apply’ command to restart docker service and apply all of your small incremental changes at convenient time.

Synopsis:

```
docker-config apply [-h]
```

Detailed description of named arguments:

```
-h, --help show this help message and exit
```

## 5.5.2 compose

Containers defined by docker compose files can be automatically started after each reboot of Edge Gateway. Admin users can provide multiple compose files, which will be stored in centrally managed location and started by special user named ‘composed’.

This command has following subcommands:

recreate	force recreation of selected or all composed containers
get	get contents of single docker-compose file
status	saves artificial compose of all currently running containers
load	load docker-compose config file into system
del	remove docker-compose config from system
set_config	replaces current compose files with new set
get_config	get docker compose configuration and store it in a file

Detailed description of named arguments:

```
-h, --help show this help message and exit
```

Examples:

load contents of compose.yml in current directory under the name ‘pump\_regulator’

```
docker-config compose load -f ./compose.yml -n pump_regulator
```

delete compose file added by above example

```
docker-config compose del -n pump_regulator
```

get all compose files configured

```
docker-config compose get_config
```

show yaml of currently running containers

```
docker-config compose status
```

## recreate

Example reason for recreation can be long lived container which holds some internal invalid state and is not working properly anymore. Another common case is need to change configuration values (e.g. proxy setting) embeded into container during its creation time — their subsequent change outside container will not be reflected unless recreation is forced.

Synopsis:

```
docker-config compose recreate [-h] [-n NAME]
```

Detailed description of named arguments:

<code>-h, --help</code>	show this help message <b>and</b> exit
<code>-n NAME, --name NAME</code>	pattern <b>for</b> names to be recreated

## get

Synopsis:

```
docker-config compose get [-h] -n NAME
```

Detailed description of named arguments:

<code>-h, --help</code>	show this help message <b>and</b> exit
<code>-n NAME, --name NAME</code>	name under which this compose file shall be stored

## status

Synopsis:

```
docker-config compose status [-h]
```

Detailed description of named arguments:

<code>-h, --help</code>	show this help message <b>and</b> exit
-------------------------	--

This option can be used to save currently running docker containers to one docker-compose file which can be later used to start same set of containers manually (for example outside Edge Gateway). This option will only export docker containers spawned by the user. Docker containers used by Azure IoTEdge daemon will not be exported. Data will be saved to a file named `docker-compose.yml`.

## Examples

```
docker-config compose status
```

## System behavior

This option will not affect the system behavior.

## load

Contents of docker compose yaml config will be loaded under name provided by -name option, and respective containers will be started immediately, and then after each reboot.

Synopsis:

```
docker-config compose load [-h] -f FILENAME -n NAME
```

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
-f FILENAME, --filename FILENAME	path of the file <b>with</b> compose yaml config
-n NAME, --name NAME	name under which this compose file shall be stored

Note that compose file will be stored in director of special user, which adds some limitations. For example relative paths will probably not work.

Examples

```
docker-config compose load --name flow_monitor --filename docker-compose.yml
```

## System behavior

This option will change the list of currently running docker containers. In addition, docker-engine will create additional network interfaces, add firewall configuration to iptables.

## del

Respective containers will be stopped and compose file removed.

Synopsis:

```
docker-config compose del [-h] -n NAME
```

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
-n NAME, --name NAME	name of compose file to be removed

## set\_config

Restore docker compose files from file. This is a permanent change (and will remove previously present compose files (if any)) If containers are not running they will be started using new configuration. If you want to restart those which are running use recreate command.

Synopsis:

```
docker-config compose set_config [-h] [-f FILENAME]
```

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
-f FILENAME, --filename FILENAME	file <b>with</b> configuration data

## get\_config

All currently present docker compose files will be stored in to file named `compose_config.json`.

Synopsis:

```
docker-config compose get_config [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

## 5.5.3 dns

Add and remove DNS servers from your docker configuration.

This command has following subcommands:

add	Add DNS to current configuration (this command requires executing 'apply' afterwards)
del	Delete DNS from current configuration (this command requires executing 'apply' afterwards)
set_config	Replace current docker DNS configuration
get_config	Store current docker DNS configuration in file <code>dockerdns_config.json</code>
show	Show current docker DNS configuration

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

Examples:

`add <IP_ADDR>` as DNS for docker

```
docker-config dns add <IP_ADDR>
```

`remove <IP_ADDR>` from list of DNS's of docker

```
docker-config dns del <IP_ADDR>
```

replace current DNS list with one from file

```
docker-config dns set_config -f <FILENAME>
```

store current configuration in file `./dockerdns_config.json`

```
docker-config dns get_config
```

display current nameservers from docker configuration

```
docker-config dns show
```

## add

Synopsis:

```
docker-config dns add [-h] ip_address
```

Detailed description of positional arguments:

```
ip_address
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

## del

Synopsis:

```
docker-config dns del [-h] ip_address
```

Detailed description of positional arguments:

```
ip_address
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

## set\_config

Synopsis:

```
docker-config dns set_config [-h] [-f FILENAME]
```

Detailed description of named arguments:

```
-h, --help      show this help message and exit
-f FILENAME, --filename FILENAME
               file with configuration data
```

## get\_config

Synopsis:

```
docker-config dns get_config [-h] [-f FILENAME]
```

Detailed description of named arguments:

```
-h, --help      show this help message and exit
-f FILENAME, --filename FILENAME
```

## show

Synopsis:

```
docker-config dns show [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

## 5.5.4 params

Configuration of docker daemon

This command has following subcommands:

show	Show <b>all</b> configured docker daemon parameters
set_config	Set config <b>for</b> docker daemon.json

Detailed description of named arguments:

-h, --help	show this help message and exit
-M MTU, --mtu MTU	Set MTU on docker network interface
-D, --debug	Enable docker debug

Examples:

sets given MTU for docker network interface (null for removal)

```
docker-config params --mtu <MTU>
```

enable docker debug mode

```
docker-config params --debug
```

## show

Synopsis:

```
docker-config params show [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

## set\_config

Synopsis:

```
docker-config params set_config [-h] [-f FILENAME]
```

Detailed description of named arguments:

-h, --help	show this help message and exit
-f FILENAME, --filename FILENAME	file <b>with</b> configuration data

## 5.5.5 auth

Add or remove authentication to different repositories.

This command has following subcommands:

add	Authenticate to private repositories
remove	Remove url to private repositories

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
------------	--

### add

Add authentication to different repositories.

Synopsis:

docker-config auth add [-h] [-u USER] [-p PASSWORD] [-U URL]
--

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
-u USER, --user USER	name of the user
-p PASSWORD, --password PASSWORD	password of the user
-U URL, --url URL	url to the private repository (default is ' <a href="https://index.docker.io/v1/">https://index.docker.io/v1/</a> ')

Examples:

docker-config auth add -u <user> -p <password> -U <url>
---

### remove

Remove authentication to the repositories by providing the url.

Synopsis:

docker-config auth remove [-h] -U URL
---------------------------------------

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
-U URL, --url URL	url to the private repository to remove

Examples:

docker-config auth remove -U <url>
------------------------------------

## 5.6 OVPN

This command has following subcommands:

add	Add new OpenVPN tunnel
remove	Remove OpenVPN tunnel
autostart	Disable/enable OpenVPN tunnel autostart
connection	Disable/enable OpenVPN tunnel connection.
get_config	Get configuration of OpenVPN tunnel <b>and</b> save it to JSON file.
set_config	Restore OpenVPN tunnel configuration <b>from file</b>
show	Display OpenVPN tunnel configuration
status	Display OpenVPN tunnel status

### 5.6.1 add

Synopsis:

```
ovpn add [-h] -f FILENAME -a {yes,no}
```

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
-f FILENAME, --filename FILENAME	
-a {yes,no}, --autostart {yes,no}	

This option can create a new tunnel configuration with an existing file. Function takes file with .ovpn extension for -f/--filename and yes or no for -a/--autostart as arguments. The autostart option defines whether the tunnel is automatically created during boot.

### Examples

To create a new configuration based on the configuration file tunnel.ovpn with autostart enabled.

```
ovpn add -f tunnel.ovpn -a yes
```

```
ovpn add --filename tunnel.ovpn --autostart yes
```

### System behaviour

This option will create a new tunnel configuration. If there is already a tunnel with the same name, CLI will ask to override the existing one.

### 5.6.2 remove

Synopsis:

```
ovpn remove [-h] -t {}
```

Detailed description of named arguments:

-h, --help	show this help message <b>and</b> exit
-t {}, --tunnel {}	

This option can remove existing tunnel. The tunnel must be the same as the configuration file name without the .ovpn extension.

## Examples

To remove configuration for tunnel ovpnTunnel.

```
ovpn remove -t ovpnTunnel
```

## System behaviour

This option will stop selected tunnel and remove its configuration file from /etc/openvpn.

### 5.6.3 autostart

Synopsis:

```
ovpn autostart [-h] -t {} -a {enable,disable,status}
```

Detailed description of named arguments:

```
-h, --help          show this help message and exit
-t {}, --tunnel {}  Tunnel config name
-a {enable,disable,status}, --action {enable,disable,status}
                     To check current autostart option select status.
```

This option can be used to control the autostart behavior. One can also check the current status with -a/--action set to status. The tunnel must be the same as the configuration file name without the .ovpn extension.

## Examples

To check current autostart for tunnel ovpnTunnel.

```
ovpn autostart -t ovpnTunnel -a status
```

To enable autostart for tunnel ovpnTunnel.

```
ovpn autostart -t ovpnTunnel -a enable
```

## System behaviour

This option will change the behavior of the tunnel during the boot process.

### 5.6.4 connection

Synopsis:

```
ovpn connection [-h] -t {} -a {enable,disable,status}
```

Detailed description of named arguments:

```
-h, --help          show this help message and exit
-t {}, --tunnel {}  Tunnel config name
-a {enable,disable,status}, --action {enable,disable,status}
                     This will only enable/disable the tunnel for current
                     session. If you want to have this connection on boot
                     please check autostart option.
```

This option can be used to control the tunnel during system operation. One can also check the current status with -a/--action set to status. The tunnel must be the same as the configuration file name without the .ovpn extension.

## Examples

To check current connection status for tunnel ovpnTunnel.

```
ovpn connection -t ovpnTunnel -a status
```

To enable tunnel ovpnTunnel.

```
ovpn connection -t ovpnTunnel -a enable
```

## System behaviour

This option will change the behavior of the tunnel during current system operation.

### 5.6.5 get\_config

Synopsis:

```
ovpn get_config [-h]
```

Detailed description of named arguments:

```
-h, --help      show this help message and exit
```

This option can be used to save current openvpn tunnels configuration to json file.

## Examples

```
ovpn get_config
```

## System behaviour

This option does not alter the system behavior or configuration.

### 5.6.6 set\_config

Synopsis:

```
ovpn set_config [-h] -f FILENAME
```

Detailed description of named arguments:

```
-h, --help      show this help message and exit
-f FILENAME, --filename FILENAME
```

This option can be used to restore openvpn tunnels configuration from json file.

## Examples

```
ovpn set_config --filename vpn.json
```

## System behaviour

This option will change the current openvpn tunnels configuration. If there is already a configuration with the same name as in the configuration file, the existing one will be overwritten.

### 5.6.7 show

Synopsis:

```
ovpn show [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

This option can be used to print current openvpn configuration to console.

## Examples

```
ovpn show
```

## System behaviour

This option does not alter the system behavior or configuration.

### 5.6.8 status

Synopsis:

```
ovpn status [-h]
```

Detailed description of named arguments:

```
-h, --help  show this help message and exit
```

This option can be used to print current openvpn tunnels status like IP address or device interface name.

## Examples

```
ovpn status
```

## System behaviour

This option does not alter the system behavior or configuration.

## 5.7 Azure modules access to a device's local storage

One can use dedicated storage on the device in order to improve reliability, especially when operating offline.

## 5.8 Link module storage to device storage

Edge Gateway has dedicated storage place `/iotedge` that one can use to store module data. To enable module local storage one has to set environmental variable `storageFolder` in module configuration. That variable has to point to a catalog inside module's container. The module catalog has to be configured to use host directory `/iotedge` in order to keep data between the device reboot or system update.

## Runtime Settings

Edge Hub

Schema Version  ⓘ

1.1

Image  ⓘ

mcr.microsoft.com/azureiotedge-hub:1.0

Image Pull Policy  ⓘ

Store and forward configuration – time to live (seconds)  ⓘ

7200

Create Options  ⓘ

```
{  
  "HostConfig": {  
    "Binds": [  
      "/iotedge/:/iotedge/storage"  
    ],  
    "PortBindings": {  
      "443/tcp": [  
        {  
          "HostPort": "443"  
        }  
      ],  
      "5671/tcp": [  
        {  
          "HostPort": "5671"  
        }  
      ],  
      "8883/tcp": [  
        {  
          "HostPort": "8883"  
        }  
      ]  
    }  
  }  
}
```

Environment Variables  ⓘ

Name	Value
storageFolder	/iotedge/storage

## 5.8.1 See more

For more information please check Microsoft Documentation available here: <https://docs.microsoft.com/en-us/azure/iot-edge/how-to-access-host-storage-from-module?view=iotedge-2018-06#link-module-storage-to-device-storage>

## 5.9 iotedge command

The iotedge tool is used to manage the IoT Edge runtime.

USAGE:

```
iotedge [OPTIONS] <SUBCOMMAND>
```

OPTIONS:

-h, --help	Print help information
-H, --host <HOST>	Daemon socket to connect to [env: IOTEDGE_HOST=] [default:unix:///var/run/
iotedge/mgmt.sock]	
-V, --version	Print version information

SUBCOMMANDS:

check	Check <b>for</b> common config <b>and</b> deployment issues
check-list	List the checks that are run <b>for</b> 'iotedge check'
help	Print this message <b>or</b> the help of the given subcommand(s)
list	List modules
logs	Fetch the logs of a module
restart	Restart a module
support-bundle	Bundles troubleshooting information
version	Show the version information

### 5.9.1 iotedge check

Check for common config and deployment issues

USAGE:

```
iotedge check [OPTIONS]
```

OPTIONS:

-c, --config-file <FILE>	Sets daemon configuration file [default: /etc/iotedge/config.yaml]
--container-engine-config-file <FILE>	Sets the path of the container engine configuration file [default:/etc/docker/daemon.json]
--diagnostics-image-name <IMAGE_NAME>	Sets the name of the azureiotedge-diagnostics image. [default:mcr.microsoft.com/azureiotedge-diagnostics:1.1.13]
--dont-run <DONT_RUN>...	Space-separated <b>list</b> of check IDs. The checks listed here will <b>not</b> be run. See 'iotedge check-list' <b>for</b> details of <b>all</b> checks.
[possible values: certificates-quickstart, config-yaml-well-formed, connect-management-uri, connection-string, container-connect-iothub-amqp, container-connect-iothub-https, container-connect-iothub-mqtt, container-default-connect-iothub-amqp, container-default-connect-iothub-https, container-default-connect-iothub-mqtt, container-engine-dns, container-engine-ipv6, container-engine-logrotate, container-engine-uri, container-local-time, edge-agent-storage-mounted-from-host, edge-hub-storage-mounted-from-host, host-connect-dps-endpoint, host-connect-iothub-amqp, host-connect-iothub-https, host-connect-iothub-mqtt, host-local-time, host-name, identity-certificate-expiry, iotedge-version, windows-host-version]	

(continued from previous page)

```

--expected-iotedged-version <VERSION>
  Sets the expected version of the iotedged binary. Defaults to the value contained in
  <http://aka.ms/latest-iotedge-stable>

-h, --help
  Print help information

-H, --host <HOST>
  Daemon socket to connect to [env: IOTEDGE_HOST=] [default:unix:///var/run/iotedge/mgmt.
  <sock>]

--iotedged <PATH_TO_IOTEDGED>
  Sets the path of the iotedged binary. [default: /usr/bin/iotedged]

--iothub-hostname <IOTHUB_HOSTNAME>
  Sets the hostname of the Azure IoT Hub that this device would connect to. If using
  <manual provisioning, this does not need to be specified.

--ntp-server <NTP_SERVER>
  Sets the NTP server to use when checking host local time. [default: pool.ntp.org:123]

-o, --output <FORMAT>
  Output format. Note that JSON output contains some additional information like OS name,
  < OS version, disk space, etc. [default: text] [possible values: json, text]

--verbose
  Increases verbosity of output.

--warnings-as-errors
  Treats warnings as errors. Thus 'iotedge check' will exit with non-zero code if it
  <encounters warnings.

```

## 5.9.2 iotedge check-list

List the checks that are run for 'iotedge check'

USAGE:

```
iotedge check-list [OPTIONS]
```

OPTIONS:

```

-h, --help      Print help information
-H, --host <HOST>  Daemon socket to connect to [env: IOTEDGE_HOST=] [default:unix:///var/run/
  <iotedge/mgmt.sock>]

```

## 5.9.3 iotedge list

List modules

USAGE:

```
iotedge list [OPTIONS]
```

OPTIONS:

```

-h, --help           Print help information
-H, --host <HOST>  Daemon socket to connect to [env: IOTEDGE_HOST=] [default:unix:///var/run/
↳ iotedge/mgmt.sock]
  
```

## 5.9.4 iotedge logs

Fetch the logs of a module

USAGE:

```
iotedge logs [OPTIONS] <MODULE>
```

ARGS:

```
<MODULE>  Sets the module identity to get logs
```

OPTIONS:

```

-f, --follow
      Follow output log

-h, --help
      Print help information

-H, --host <HOST>
      Daemon socket to connect to [env: IOTEDGE_HOST=] [default:unix:///var/run/iotedge/mgmt.
↳ sock]

--since <DURATION or TIMESTAMP>
      Only return logs since this time, as a duration (1 day, 90 minutes, 2 days 3 hours 2
↳ minutes), rfc3339 timestamp, or UNIX timestamp [default: "1 day"]

--tail <NUM>
      Number of lines to show from the end of the log [default: all]

--until <DURATION or TIMESTAMP>
      Only return logs up to this time, as a duration (1 day, 90 minutes, 2 days 3 hours 2
↳ minutes), rfc3339 timestamp, or UNIX timestamp. For example, 0d would not truncate any logs, u
↳ while 2h would return logs up to 2 hours ago
  
```

## 5.9.5 iotedge restart

Restart a module

USAGE:

```
iotedge restart [OPTIONS] <MODULE>
```

ARGS:

```
<MODULE>  Sets the module identity to restart
```

OPTIONS:

```

-h, --help           Print help information
-H, --host <HOST>  Daemon socket to connect to [env: IOTEDGE_HOST=] [default:unix:///var/run/
↳ iotedge/mgmt.sock]
  
```

## 5.9.6 iotedge support-bundle

Bundles troubleshooting information

USAGE:

```
iotedge support-bundle [OPTIONS]
```

OPTIONS:

```
-e, --include-edge-runtime-only
  Only include logs from Microsoft-owned Edge modules

-h, --help
  Print help information

-H, --host <HOST>
  Daemon socket to connect to [env: IOTEDGE_HOST=] [default:unix:///var/run/iotedge/mgmt.
-sock]

--iothub-hostname <IOTHUB_HOSTNAME>
  Sets the hostname of the Azure IoT Hub that this device would connect to. If using manual provisioning, this does not need to be specified.

-o, --output <FILENAME>
  Location to output file. Use - for stdout [default: support_bundle.zip]

-q, --quiet
  Suppress status output

--since <DURATION or TIMESTAMP>
  Only return logs since this time, as a duration (1d, 90m, 2h30m), rfc3339 timestamp, or UNIX timestamp [default: "1 day"]

--until <DURATION or TIMESTAMP>
  Only return logs up to this time, as a duration (1 day, 90 minutes, 2 days 3 hours 2 minutes), rfc3339 timestamp, or UNIX timestamp. For example, 0d would not truncate any logs, while 2h would return logs up to 2 hours ago
```

## 5.9.7 iotedge version

Show the version information

USAGE:

```
iotedge version [OPTIONS]
```

OPTIONS:

```
-h, --help      Print help information
-H, --host <HOST>  Daemon socket to connect to [env: IOTEDGE_HOST=] [default:unix:///var/run/
-iotedge/mgmt.sock]
```

# 6 Web Interface

## 6.1 EdgeGateway WebUI Documentation

This document walks you through enabling, configuring, and using the EdgeGateway (eG-OS) WebUI to monitor and manage your device.

1. *Getting Started*
  - *Enabling the WebUI Service*
  - *Accessing the WebUI*
2. *Home Dashboard*
3. *Device Configuration*
4. *Network Settings*
5. *Cellular Settings*
6. *System Update*
7. *System Logs*
8. *Logging Out*

---

### 6.1.1 Getting Started

#### Enabling the WebUI Service

Use the CLI to enable and start the WebUI service:

```
device webgui enable
device webgui status
```

A successful status response looks like:

```
{
  "webgui": {
    "is_running": true,
    "is_enabled": true,
    "http_redirect": true,
    "subservice_status": "OK",
    "port": 48366
  }
}
```

Additional commands:

Command	Description
device webgui disable	Disable WebUI
device webgui config --port <port>	Change listening port
device webgui redirect --enable	Enable HTTP→HTTPS redirection
device webgui redirect --disable	Disable HTTP→HTTPS redirection

## Accessing the WebUI

1. Determine the device IP address:


```
nm show
```

2. Open your web browser and navigate to:

```
https://<DEVICE_IP>:<PORT>
```

3. Log in with your administrator credentials.

### 6.1.2 Home Dashboard



The **Home** dashboard provides real-time system statistics:

- **System Information:** Hardware model, OS version, CPU count.
- **Disk Space:** Pie charts showing free vs. used space for ROOTA and DATA partitions.
- **System Load average**
- **CPU utilization**
- **Memory Usage:** Used, buffered, and cached memory with percentage.
- **Network Interfaces:** Table of interface names and assigned IP addresses.


Use the sidebar menu to switch between sections:

- **Home:** Dashboard overview.
- **Device Configuration:** Import/export configuration, reboot device.
- **Network Settings:** Configure LAN interfaces and VLANs.
- **Cellular Settings:** Manage cellular modem (if supported).

- **System Update:** Upload and apply firmware updates.
- **System Logs:** View system logs.
- **Logout:** Securely end your session.

---

### 6.1.3 Device Configuration



Welcome to EG management panel

EdgeGateway

Device configuration

Drag and drop files here or click to select files

Select files

Download config backup

Reboot


© Welotec 2025

Manage your device's configuration files:

- **Upload Configuration:** Drag-and-drop or select a .conf file to apply settings.
- **Download Backup:** Export the current running configuration.
- **Reboot:** Restart the device properly.

---

## 6.1.4 Network Settings



The screenshot shows the EdgeGateway management panel. The left sidebar has links for Home, Device configuration, Network settings (selected), Cellular settings, System update, System logs, and Logout. The main content area shows the following sections:

- Interface lan1 configuration:** Includes fields for IPv4 address (192.168.2.1), Network subnet (24), Default gateway (Edit me), and DNS (Edit me). A checkbox for Enable DHCP is present. A "Save" button is at the bottom.
- VLANs configuration for lan1:** A table with three rows: IP address, Subnet in CIDR format, and Gateway. The Gateway row has a green checkmark and an "Add new" button.
- Interface lan2 configuration:** Includes a checkbox for Enable DHCP.

Configure LAN interfaces and VLANs:


### 1. Interface Configuration

- Enable DHCP or set a **Static IPv4 Address, Subnet Mask (CIDR), Gateway, and DNS**.

### 2. VLANs

- Add multiple VLAN entries per interface.
- Specify VLAN IP, subnet (CIDR), and gateway.

## 6.1.5 Cellular Settings



The screenshot shows the 'Interface cellular1 configuration' page of the EdgeGateway management panel. The left sidebar lists navigation options: Home, Device configuration, Network settings, Cellular settings (which is selected and highlighted in blue), System update, System logs, and Logout. The main content area is titled 'Interface cellular1 configuration' and contains the following fields:

- Enable cellular connection
- Access number:
- APN:
- Username:
- Password:
- PIN:


A blue 'Save' button is located at the bottom right of the form. The footer of the page includes the text '© Welotec 2025'.

Configure cellular connectivity on devices that include a cellular modem:

- 1. Enable Cellular Connection** Toggle the switch to activate the cellular interface.
- 2. Access Number** Enter the dial-in number provided by your carrier (e.g., \*99#).
- 3. APN** Specify the Access Point Name supplied by your mobile network operator.
- 4. Username** If required, provide the APN username.
- 5. Password** If required, provide the APN password.
- 6. PIN** Enter the SIM card PIN to unlock the SIM (if PIN lock is enabled).
- 7. Save** Click **Save** to apply and persist your cellular settings.

*This section applies only if your hardware supports cellular interfaces.*

## 6.1.6 System Update



Upload and install new firmware images (.swu) to keep your EdgeGateway up-to-date:

1. **Firmware Upload:** Drag-and-drop or click to select the .swu file.
2. **Reset Selection:** Clear the current file choice.

---

## 6.1.7 System Logs

View system logs to troubleshoot or audit device activity. Logs include timestamps, unit identifiers, and message details.

---

## 6.1.8 Logging Out

Click **Logout** in the sidebar to securely end your session.

---

## 6.2 Central Device Management via SMART EMS

With the Welotec SMART EMS Container users benefit from a straight-forward device management system for Welotec devices like 4G LTE Routers and Edge Gateways. It enables a remote management of device configurations and firmware, deployment of zero-touch mass rollouts, and generation device diagnostics, on demand. Learn more about our solution here: <https://www.welotec.com/product/welotec-smart-ems/>

The functionality of Welotec SMART EMS can be extended by our solution VPN Security Suite. This enables building secure VPN infrastructures and creation of E2E-connections with devices and machines in the field. Learn more about our solution here: <https://www.welotec.com/product/welotec-vpn-security-suite/>

In case of interest, please get in touch: <https://www.welotec.com/contact/>

# 7 OS Updates

Updates are being provided regularly by Welotec and can be downloaded in our [Download Service](#) The following options are available for updating the system

## 7.1 ‘device swupdate’ Command

Upload the SWU-file for your platform for example using SCP Please check swupdate Command in ‘device’ section for further details

## 7.2 Update Page in WebUI

For updates via WebUI please check “System Update” section in “EdgeGateway WebUI Documentation” chapter

## 7.3 SMART EMS

Please check SMART EMS Section for further details.

# 8 Factory Reset

## 8.1 Via CLI

Use 'device erase everything' Command to reset the device

## 8.2 Via Power button

If your device has a power button this can be used to reset the device. Press the power button 3 times in the following order:

```
press button -> wait -> press button -> wait -> press button
```

Time elapsed between two button presses must be at least 5 seconds but must not exceed 15 seconds. The device will indicate the successful button press with an acoustic signal for each press:

```
button press 1: 1 beep
button press 2: 2 beeps
button press 3: 3 beeps
```

## 9 OSS Clearings

The copyrights for certain portions of the Software may be owned or licensed by other third parties (“Third Party Software”) and used and distributed under license. The Third Party Notices includes the acknowledgements, notices and licenses for the Third Party Software. The Third Party Notices can be viewed via CLI please use ‘device oss’ Command to display them on the screen. The Third Party Software is licensed according to the applicable Third Party Software license notwithstanding anything to the contrary in this Agreement. The Third Party Software contains copyrighted software that is licensed under the GPL/LGPL or other copyleft licenses. Copies of those licenses are included in the Third Party Notices. Welotec’s warranty and liability for Welotec’s modification to the software shown below is the same as Welotec’s warranty and liability for the product this Modifications come along with. It is described in your contract with Welotec (including General Terms and Conditions) for the product. You may obtain the complete Corresponding Source code from us for a period of three years after our last shipment of the Software by sending a request letter to:

Welotec GmbH, Zum Hagenbach 7, 48366 Laer, Germany

Please include “Source for Welotec Edge Gateway / egOS” and the version number of the software in the request letter. This offer is valid to anyone in receipt of this information.

You can find OSS clearings under following link: [OSS Licenses](#)